


Data Sheet | Item Number: 706-3340/401-200
 System cable; for Schneider Modicon M340; 4 analog inputs (voltage), var. 1;
 Length: 2 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-3340/401-200>



Color coding acc. to DIN VDE 47100	15 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	0+	1	UI0
Brown	2	0-	2	Com0
Green	3	1+	7	UI1
Yellow	4	1-	8	Com1
Grey	5	2+	11	UI2
Pink	6	2-	12	Com2
Blue	7	3+	17	UI3
Red	8	3-	18	Com3
Black	9	nc	nc	nc
Violet	10	nc	nc	nc
Grey-Pink	11	nc	nc	nc
Red-Blue	12	nc	nc	nc
White-Green	13	nc	nc	nc
Brown-Green	14	nc	nc	nc
White-Yellow	15	nc	nc	nc
Shield		Connected to Sub-D		

Similar to illustration

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Electrical data

Inputs/outputs	2 x 8 analog inputs; voltage
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Compatibility

Schneider	
Schneider Modicon M340	BMX AMI 0410 BMX AMO 0410

Connection Data

Cable type	LiYCY	Connection 1	
Color code	per DIN VDE 47100	Pluggable connector	D-subminiature female connector
		Pole number 1	15
		Connection type	System
		Wire cross-section	0.25 mm ²

Connection 2

Connector	Schneider BMXFTB2020
Pole number	20
Connection type	System
Wire cross-section	0.25 mm ²

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	193 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

Product Group	30 (WAGO France)
PU (SPU)	1 pcs
Packaging type	not specified
Country of origin	FR
GTIN	4045454869120
Customs tariff number	85444290900

Product Classification

UNSPSC	26121629
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
706-3340/401-200



Documentation

System Description

WAGO System Wiring,
Selection Guide

pdf
533.15 KB

