


PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55. DALI DIM max 20 luminaires
0041542



Product features

- PIR sensor with switching and dimming capability for controlling up to 20 DALI luminaires. On/off and dim via lux sensing. Absence/presence detection. Adjustable time delay (10sec to 99min). Maintained illuminance capabilities. Up to 7m detection radius at 2.8m mounting height. Programmable via handset. Mounting accessories available. 10A maximum load.



PRODUCT OVERVIEW

Product name	Compact PIR detector - lux sensing. Time delay - IP55. DALI DIM max 20 luminaires
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
Max load (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Output protocol	DALI, DSI
Number of channels	2
IP rating	IP40
Product EAN number	5410288415420

DATA TABLE

General data

Product name	Compact PIR detector - lux sensing. Time delay - IP55. DALI DIM max 20 luminaires
Configured without PC	Yes
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC000533

Electrical data

Max load (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor

PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55. DALI DIM max 20 luminaires
0041542

Output protocol	DALI, DSI
Number of channels	2
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Physical data

IP rating	IP40
Nominal Product Length (mm)	76
Nominal Product Width (mm)	76
Nominal Product Height (mm)	68.5
Cutout Dimensions (W x L in mm or Diameter in mm)	64
Weight (kg)	0.111
Recessed Depth (mm)	65

Packaging

Single packaging type	Carton
Product EAN number	5410288415420
Packaging single length / height (cm)	9.5
Packaging single width (cm)	9.5
Packaging single depth (cm)	7.5
Units per outer package	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

Safety data

Optimal operating condition (°C)	-10-35
----------------------------------	--------

TECHNICAL DRAWINGS

