


## PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55. 1-10V DIM max 10 luminaires

0041543



### Product features

- PIR sensor with switching and dimming capability for controlling up to 10 1-10V luminaires. On/off and dim via lux sensing. Absence/presence detection. Adjustable time delay (10sec to 99min). Maintained illuminance capabilities. Up to 7m detection radius at 2.8m mounting height. Programmable via handset. Mounting accessories available. 10A maximum load.



## PRODUCT OVERVIEW

Product name	Compact PIR detector - lux sensing. Time delay - IP55. 1-10V DIM max 10 luminaires
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
Max load (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Output protocol	1-10V
Number of channels	2
IP rating	IP40
Product EAN number	5410288415437

## DATA TABLE

### General data

Product name	Compact PIR detector - lux sensing. Time delay - IP55. 1-10V DIM max 10 luminaires
Configured without PC	Yes
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC000533

### Electrical data

Max load (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor

## PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55. 1-10V DIM max 10 luminaires

0041543

Output protocol	1-10V
Number of channels	2
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

### Physical data

IP rating	IP40
Nominal Product Length (mm)	76
Nominal Product Width (mm)	76
Nominal Product Height (mm)	68.5
Cutout Dimensions (W x L in mm or Diameter in mm)	64
Weight (kg)	0.113
Recessed Depth (mm)	65

### Packaging

Single packaging type	Carton
Product EAN number	5410288415437
Packaging single length / height (cm)	9.5
Packaging single width (cm)	9.5
Packaging single depth (cm)	7.5
Units per outer package	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

### Safety data

Optimal operating condition (°C)	-10-35
----------------------------------	--------

## TECHNICAL DRAWINGS

