

GLOBAL TRAC PULSE END FEED-R BLACK
XTSC611-2



Features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate end feed that is applicable for three-circuit track systems where the polarity ridge is in the right side. Dimensions - 105 x 32 x 33 mm (L x W x H), black (RAL 9005).

Product Overview

Product name	GLOBAL TRAC PULSE END FEED-R BLACK
Technology	Accessory
Housing	PC Polycarbonate
Light colour	N/A
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532383
Warranty	5 years

Data table

GENERAL DATA	
Product name	GLOBAL TRAC PULSE END FEED-R BLACK
Technology	Accessory
Housing	PC Polycarbonate
Operating temperature range (°C)	0°C...+25°C
Warranty	5 years

GLOBAL TRAC PULSE END FEED-R BLACK XTSC611-2

OPTICAL DATA

Light colour	N/A
--------------	-----

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	105
Nominal Product Width (mm)	32
Weight (kg)	0.076

PACKAGING

Single packaging type	Plastic
Product EAN number	6410014532383
Packaging single width (cm)	2.7
Packaging single depth (cm)	3.2
DUN14 (outer)	06410014532383
Packaging outer length / height (cm)	40.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No