

Global Trac Electrical Accessories
GLOBAL TRAC PULSE END FEED-L WHITE
XTSC612-3



Product features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate end feed that is applicable for three-circuit track systems where the polarity ridge is in the left side. Dimensions - 105 x 32 x 33 mm (L x W x H), white (RAL 9010).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532420

DATA TABLE

General data	
Product name	GLOBAL TRAC PULSE END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC002556
Warranty	5 years
Optical data	
Light colour	N/A
Electrical data	
Dimmable	Yes
Physical data	
Housing colour	RAL 9010 - Pure white



Global Trac Electrical Accessories

GLOBAL TRAC PULSE END FEED-L WHITE
XTSC612-3

IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	105
Nominal Product Width (mm)	32
Nominal Product Height (mm)	33
Weight (kg)	0.076

Packaging

Single packaging type	Plastic
Product EAN number	6410014532420
Packaging single length / height (cm)	15.5
Packaging single width (cm)	2.7
Packaging single depth (cm)	3.2
DUN14 (outer)	06410014532420
Units per outer package	50
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes