

GLOBAL TRAC PULSE END FEED-L WHITE
XTSC612-3



Features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate end feed that is applicable for three-circuit track systems where the polarity ridge is in the left side. Dimensions - 105 x 32 x 33 mm (L x W x H), white (RAL 9010).

Product Overview

Product name	GLOBAL TRAC PULSE END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
Light colour	N/A
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532420
Warranty	5 years

Data table

GENERAL DATA

Product name	GLOBAL TRAC PULSE END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
Operating temperature range (°C)	0°C...+25°C



GLOBAL TRAC PULSE END FEED-L WHITE
XTSC612-3

Warranty	5 years
----------	---------

OPTICAL DATA

Light colour	N/A
--------------	-----

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	105
Nominal Product Width (mm)	32
Weight (kg)	0.076

PACKAGING

Single packaging type	Plastic
Product EAN number	6410014532420
Packaging single width (cm)	2.7
Packaging single depth (cm)	3.2
DUN14 (outer)	06410014532420
Packaging outer length / height (cm)	40.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No