

## Microwave detectors - Ceiling-mounted and tilt adjustable

### Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)

0041579



#### Product features

- Adjustable/tiltable ceiling recessed microwave presence/absence detector. Lux level sensing. Time delay function. Infrared override. Dual sensitivity offers configurable ON and OFF motion sensitivity. Programmable using programming handsets. Wide range of accessories including surface mounting backboxes and wall mounting bracket. Multiples can be wired in parallel for L-shaped corridors. IP40. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.



### PRODUCT OVERVIEW

Product name	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
Warranty	3 years
Max load (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Output protocol	Switched
Number of channels	1
IP rating	IP40
Product EAN number	5410288415796

### DATA TABLE

#### General data

Product name	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)
Configured without PC	Yes
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533
Warranty	3 years

#### Electrical data

Max load (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor

## Microwave detectors - Ceiling-mounted and tilt adjustable

*Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)*  
0041579

Output protocol	Switched
Number of channels	1
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

### Physical data

IP rating	IP40
Nominal Product Length (mm)	85
Nominal Product Width (mm)	85
Nominal Product Height (mm)	92
Cutout Dimensions (W x L in mm or Diameter in mm)	74
Weight (kg)	0.15
Recessed Depth (mm)	92

### Packaging

Single packaging type	Carton
Product EAN number	5410288415796
Packaging single length / height (cm)	10.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	10.0
Units per outer package	1
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	47.0

### Safety data

Optimal operating condition (°C)	-10-50
----------------------------------	--------

## TECHNICAL DRAWINGS

