

## Global Trac Pulse GLOBAL TRAC PULSE 2M BLACK XTSC6200-2



### Product features

- Global Trac Pulse accessory - 3 Circuit Track 16A/400V, circuits can be controlled individually, control 2 Circuit 1A/50V FELV AC, DALI (FELV), DMX, LON, EIB, 1-10 V etc. compatible., aluminum body, suitable for surface mounting, 2000 x 31.5 x 32.5 mm (L x W x H), 1.700 kg, black (RAL 9005).



### PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE 2M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC000101
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014531492

### DATA TABLE

#### General data

Product name	GLOBAL TRAC PULSE 2M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC000101
Warranty	5 years

#### Optical data

Light colour	N/A
--------------	-----

#### Electrical data

Dimmable	Yes
----------	-----

#### Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02

## Global Trac Pulse GLOBAL TRAC PULSE 2M BLACK XTSC6200-2

Nominal Product Length (mm)	2000
Nominal Product Width (mm)	31.5
Nominal Product Height (mm)	32.5
Cutout Dimensions (W x L in mm or Diameter in mm)	2000
Weight (kg)	1.7

### Packaging

Single packaging type	Carton
Product EAN number	6410014531492
Packaging single length / height (cm)	200.0
Packaging single width (cm)	3.15
Packaging single depth (cm)	3.25
DUN14 (outer)	06410014531492
Units per outer package	4
Packaging outer length / height (cm)	200.0
Packaging outer width (cm)	12.8
Packaging outer depth (cm)	3.6

### Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes