

Splashproof garden post essential with double socket outlet, side earthing, black, IP55

761-36855

4 year warranty

The garden post essential includes two horizontal prewired socket outlets (16 A/250 Vac) with side earthing, shutters, plug-in terminals and two inputs. It has an IP55 protection degree and is equipped with a spike that needs to be driven directly into the earth. Its functional design makes the garden post a perfect fit for outdoor applications that require two angled plugs and outdoor areas, such as gardens and flower beds. Moreover, the entire unit is splashproof, which makes it extremely well-suited for use in damp areas and demanding environments.

- High-quality materials
- IP55
- Easy installation
- Authentic and sleek design
- Firm installation in the ground
- Pre-wired horizontal socket outlets that can accommodate two angled plugs
- Multi-layer cable glands that also serve as blind stops IP68 and that are suited for 4 to 15 mm cables
- Plug-in terminals with a long life span
- Protruding top edge to shield the socket outlets
- Cut-outs for cable routing straps
- Passage for ground cable

Technical data

Splashproof garden post essential with double socket outlet, side earthing, black, IP55. Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed.

- Function: – socket outlet
 - contact buses with a large contact surface that do not rest on the base in order to be connected
- Maximum MCB rating: 16 A (limited by national installation rules)
- Sealing: The cover has an integral closure and is hermetically sealed onto the appropriate box.
- Number of mechanisms: 2
- Material finishing: The box is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS.
- Material earthing side earthing in high quality brass
- Material housing: stainless steel
- Cable space
 - 12.7 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box
 - a snap connector holds the wired mechanism in place
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires



niko

- Wire capacity
 - all connection terminals at the top side of the base
 - up to 2 x 2.5 mm² wire per terminal
- Material earthing: side earthing in high quality brass
- Stripping length
 - 14 mm stripping length
 - indelibly indicated at the rear side: stripping length
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is mass-dyed, black (RAL 9005)
- Marking: CE

$\frac{h}{2}$ 16 A
250 Vac



Dimensions

