

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM
0041581



Product features

- Adjustable/tiltable ceiling recessed microwave presence/absence detector. 1-10V Direct dimming for controlling up to 10 luminaires. Lux level sensing. Time delay function. Infrared override. Dual sensitivity offers configurable ON and OFF motion sensitivity. Programmable using programming handsets. Wide range of accessories including surface mounting backboxes and wall mounting bracket. Maintained illuminance capabilities. Scene setting and recall using user handset. Lamp burn in feature. IP40. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.



PRODUCT OVERVIEW

Product name	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
Max load (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor
Output protocol	0-10V
Number of channels	2
IP rating	IP40
Product EAN number	5410288415819

TECHNICAL DRAWINGS

