GLV 032-12

GOODWE

SMT50-60 series

C10/26 - DECLARATION OF CONFORMITY for power-generating units GLV ed2.1.2 (12/2019)

for the application of annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019)



The undersigned,

Manufacturer:

Address:

GoodWe Technologies Co., Ltd.

No. 90 ZiJin Rd., New District, Suzhou,

215011, China

Represented by:

Country:

email: Telephone: Tao Jiang

CHINA

tao. jiang@goodwe. com 0086 0150 5159 0076

FINAL

the following conditions:

- 1. The power-generating unit complies with the relevant requirements set out in annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019).
- 2. In order to substantiate this, a separate technical file has been submitted at least for each separate product series of the 'C10/26 list of power-generating units' of this homologation application. Each technical file shall be drawn up on the basis of a checklist Annex D, duly and correctly completed by the manufacturer, accompanied by all the required proof of conformity.
 - 2.1 For technical requirements for which the required proof of conformity (column J in checklist annex D) is a declaration of honour by the manufacturer, the manufacturer declares by signing and dating this declaration of conformity the correctness of the information (conform conform / not applicable) provided by him or her in columns K, L and M of this checklist.
 - 2.2. For technical requirements for which the required proof of conformity (column J in checklist Annex D) is a test report or a certificate necessary test reports and/or certificates are available * in the technical file:
 - Certificates have been issued by an EN 45011 (or ISO 17065:2012) certification body accredited for these materials.
 - Test reports have been established by an ISO 17025:2005 or ISO 17065:2012 laboratory accredited for these tests. file.

Done at:

On:

Suzhou, China

01-02-2023

(stamp manufacturer & signature)

江湾

Homologated by Synergrid on: 1000 1203 Stamp Synergrid & signatSMENERGRID a.s.b.l.-v.z.w.

Galerie Ravensteingalerij 4/2 BE-1000 Bruxelles/Brussel

T.V.A/B.T.W BE 0402.958.091

* Transition period till 01/05/2020 (see exceptions in chapter 3 of C10/11 ed 2.1 (01/09/2019)):

If at the time of submission of this homologation application it is not yet possible to submit all the necessary certificates and/or test reports (exception 3), or that the units do not yet have all the required characteristics (exceptions 1 and 2), a <u>temporary homologation</u> may be granted. All necessary certificates and/or test reports must be in the possession of Synergrid at the latest on 30/04/2020 in order to obtain a final homologation. if this is not the case, the temporary C10/26 homologation will be withdrawn.

POWER-GENERATING UNITS TO BE HOWOLOGATED FOR LIST C10/26 ACCORDING TO THE REQUIREMENTS OF ANNEX D OF THE TECHNICAL PRESCRIPTION C10/11 ed2. 1 (01/09/2019) 2. C10/26 list with power generating units in accordance with annex D of C10/11 ed2. 1 (01/09/2019) Checklist ed 2. 1. 2 (12/2019)

1	2	3	4	5	6	7	- 8	9	10			11				12		1		13		14	15
SYNERGRID reference number (GLVxxx-yy-zzzz)	BRAND NAME	Name of the product SERIES	REFERENCE of the model / type of the unit	FIRMWARE t VERSION	ONLY for units (suitable for) energy storage: Name and reference of the power control system		POWER			ADDITIONAL CHARACTERISTICS				rics				APPLICATION			ON	Synergrid approval date	
								-3.		D,3	-	D,6,2	D.7.2	0	D7.1	0 9.1	D.9.1			1		N D	
					power control system type EnFluRi	other power control system	P _{st.} , rated (active) power (W)	S _{max} maximum apparent power (VA)	1-phase or 3-phase	or 3-phase	or 3-phase	in installation a TMW integrated automatic separation system	additional operating frequency range (51,5 Hz - 52,5 Hz) "RfG type B ready" = suitable for use	power response to underfrequency	active power reduction P(U)	compliant power control system provided (e.g. EnFluRt)	only homologated for "small power	only homologated for	eystem according to \$2.1.1 only homologated for	1 1	Wind energy	Energy storage	Backup power system
SLV032-12- 001	GOODWE	SMT50-60 series	GW50KS-MT	V1.03.03.13 or higher			50000	55000	3-phase		X	X	х	+	*	+	- 4	х	+	H	+		
SLV032-12- 002	GOODWE	SMT50-60 series	GW60KS-MT	V1.03.03.13 or higher			60000	66000	3-phase		х	х	х					х					
																		Н	+	Н	1		
																\pm	+	Н	\pm	\pm	\pm		
												\vdash		1		+		H		Н			
														-	-	+	+	Н	+	Н	H		
											+	\vdash		-	-	-	+	Н		S	YN	RGRII) a.s.b
										H				\exists	-	+	-	Н	-	Ġа	ler	RGRII Rave	nstein
											\perp			4		1	1	H		В	Ξ-1	000 B	xelles
																		\vdash	T	.V.	A.//	T.W	BE NA



EXPLANATIONS FOR THE COMPLETION OF THE TABLE

Column	Title	Remarks
1	SYNERGRID reference number (GLVxxx-yy-2222)	In the case of a positive tomologation, each C10/26-homologated power-generating unit is given a unique Synergrid reference number xxx - unique reference or the manufacturer yy - serial number of manufacturer xxx's record xxx zazz - unique unit reference for the manufacturer xxx Note: "GLV" is the internal Synergrid-abbreviation for Declaration of Conformity, based on the Dutch word "Gelijkvormigheideverklaring".
2	Brand name	Brand name under which the unit is marketed on the Belgian market,
3	Name of the product series	Name of the product range. Note: For each separate product range (or each group of units with common characteristics) a separate checklist according to Appendix D is required (sheet 3) together with the corresponding conformity proof documents.
4	Reference of the model	Unique product name or reference. Units of the same product range must be unequivocally distinguished from each other through this name or reference.
5	Firmware version	Reference of the firmware version of the unit,
h	power control system type EnFluki	This case is only applicable for units (suitable for) energy storage, provided with a poter control system of type Eachult: Nume and reference of the power control system at type Eachult, compliant to the requirements in Clo 11 edg-1 (01/09/2010) \$4.1.7 and \$7.41.2.1
7.	other power control	This case is only applicable for units (suitable for) energy storage, provided with a power control system of another type than for latt: Name and reference of the power control styles, comprised to the requirements in ClO 11 edg. 1 (01/09/2019) § 7, 11, 2, 2
8	Pat, lated (active)	Active (electrical) power in 6 at the terminals of the unit, as stated on the technical sheet / data sheet / brochure and manuplate. (For photovultare invertors: see also definition in \$3.2,5 of 180 62894 2016-11)
9	Smax - maximum apparent	Maximum apparent (electrical) power at the terminals of the unit, as stated on the certificate / the test report / the technical sheet / data sheet / brochure.
30	1-phase or 3-phase	indicate whether the unit is single- or three-phase. This characteristic refers to the unit itself, not to the nature of the connection to the distribution network to which the unit can be connected.
641	Additional characteristics	In these volumns optional additional characteristics of the units are indicated, following the information in checklist annex D and the corresponding technical file. Put an "X" at each relevant additional characteristic, Note: Only units < 1 MW that are "type B ready" muy be applied in an installation > 1 MW (installation "type B" according to the European Network Code RfG). A unit < 1 MW is only "type B ready" if it complies with all optional properties ticked in column I of the checklist Annex D.
13	Limitations	These columns specify limitations of the units to their application in certain types of installations, in accordance with the information in the checklist in annex D and the corresponding technical file. Put an "X" to each relevant limitation.
144	Application	Indicate the applications for which the unit is suitable, Include an "X" with each application for which the unit can be used.
(1)	Synergrid approval date Temporary homologation (expires on 01/05/2020)	Date on which the submitted homologation file was approved by Synergrid for a limited period of time, A temporary homologation is granted if the applicant invokes exceptions in chapter 3 of ClO/11 ed2, 1 (01/09/2019) and has not yet submitted all the test reports required for a definitive homologation with his homologation application (exception 3), or if the units do not yet have all the required properties (exceptions 1 and 2). The expiry date for a temporary homologation is 01/05/2020 - see conditions in chapter 3 of ClO/11 ed.2.1 (01/09/2019).
115	Synergrid approval date Final homologation	Date on which the submitted homologation file was definitely approved by Synergrid. A final approved will be granted as soon as Synergrid has a fully compliant homologation dossier. A final homologation only remains valid under the following conditions: No changes that have an influence on the initial approval are made to (the production of) the units. There is no new edition of prescription CIO/11. The validity date of the test reports in the technical file submitted for approval has not been exceeded. See also the general Synergrid procedure SI/OI for homologation of material, which is applicable. (1)

SYNERGRID a.s.b.l.-v.z.w.
Galerie Ravensteingalerij 4/2
BE-1000 Bruxelles/Brussel
T.V.A./B.T.W BE 0402.958.091

(1) - S1/01 Technical specification; procedure for application for bossologation and renewal of bossologation of materials

江湾

