

SPLIT-S26: Split ring for compression fittings (not for EK) Ø26



Commercial information

The body of the Henco fittings is made from brass CuZn40Pb2 (CW617N). The fittings are provided with O-rings and a union nut. The compression fittings have a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

Henco screw/compression fittings can be used for all applications with a maximum working pressure up to 10 bar, except for pipes which are built in floors or walls.

The body of the Henco screw/compression fittings is manufactured from brass. The fittings are provided with O-rings and a union nut with a clamping ring. Just like the brass press fittings they are fitted with a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

As in the compression and press fittings range, there are a number of fittings available which allow you to connect copper or steel pipes to Henco pipes.

Basic unit dimensions

Height	10 mm
Length	30 mm
Width	30 mm
Net weight	0.005 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material	Brass	Inner diameter	26 Millimetre
Suitable for copper tube	✘		
Suitable for steel tube	✘		
Suitable for stainless steel tube	✘		
Suitable for aluminium tube	✘		
Suitable for plastic tube	✔		
Suitable for plastic multi-layer pipes	✔		
System specific	✔		