


## Global Trac Electrical Accessories

### GLOBAL TRAC PULSE L FEED IN WHITE

### XTSC634-3



#### Product features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate L-feed that is applicable for three-circuit track systems where the polarity ridge is in the inner side. Dimensions - 99 x 99 x 33 mm (L x W x H), white (RAL 9010).



#### PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE L FEED IN WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532499

#### DATA TABLE

##### General data

Product name	GLOBAL TRAC PULSE L FEED IN WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC002556
Warranty	5 years

##### Optical data

Light colour	N/A
--------------	-----

##### Electrical data

Dimmable	Yes
----------	-----

##### Physical data

Housing colour	RAL 9010 - Pure white
----------------	-----------------------

## Global Trac Electrical Accessories

*GLOBAL TRAC PULSE L FEED IN WHITE*  
XTSC634-3

IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	99
Nominal Product Width (mm)	99
Nominal Product Height (mm)	33
Weight (kg)	0.12

### Packaging

Single packaging type	Plastic
Product EAN number	6410014532499
Packaging single length / height (cm)	16.7
Packaging single width (cm)	16.7
Packaging single depth (cm)	0.32
DUN14 (outer)	06410014532499
Units per outer package	25
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	25.0

### Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes