

GLOBAL TRAC PULSE L FEED OUT BLACK XTSC635-2



Features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate L-feed that is applicable for three-circuit track systems where the polarity ridge is in the outer side. Dimensions - 99 x 99 x 33 mm (L x W x H), black (RAL 9005).

Product Overview

Product name	GLOBAL TRAC PULSE L FEED OUT BLACK
Technology	Accessory
Housing	PC Polycarbonate
Light colour	N/A
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532512
Warranty	5 years

Data table

GENERAL DATA

Product name	GLOBAL TRAC PULSE L FEED OUT BLACK
Technology	Accessory
Housing	PC Polycarbonate
Operating temperature range (°C)	0°C...+25°C

GLOBAL TRAC PULSE L FEED OUT BLACK XTSC635-2

Warranty	5 years
----------	---------

OPTICAL DATA

Light colour	N/A
--------------	-----

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	RAL 9005 - Jet black
----------------	----------------------

IP rating	IP20
-----------	------

IK rating	IK02
-----------	------

Nominal Product Length (mm)	99
-----------------------------	----

Nominal Product Width (mm)	99
----------------------------	----

Weight (kg)	0.12
-------------	------

PACKAGING

Single packaging type	Plastic
-----------------------	---------

Product EAN number	6410014532512
--------------------	---------------

Packaging single width (cm)	16.7
-----------------------------	------

Packaging single depth (cm)	0.32
-----------------------------	------

DUN14 (outer)	06410014532512
---------------	----------------

Packaging outer length / height (cm)	40.0
--------------------------------------	------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----