



### Features

- Compact and elegant design Suitable replacement for halogen, incandescent and compact fluorescent ball lamps Instant light at the flick of a switch Uniform light distribution Good colour rendering (CRI 80) Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas Lower maintenance costs 15,000 hours average rated life

### Product Overview



Product name	ToLEDo Ball V7 806LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	6.5
Power consumption (W)	6.5
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288296296
Warranty	3 years

## ToLEDo Ball V7 806LM 827 B22 SL 0029629

Useful luminous flux (#use)

806

### Technical drawings



### Data table

#### GENERAL DATA

Product name	ToLEDo Ball V7 806LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years

### OPTICAL DATA

Useful luminous flux (#use)	806
Luminous flux (Rated) (lm)	806
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Power consumption (W)	6.5
Wattage (W)	6.5
Equivalent watt (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	2.8
Inrush Duration (µs)	380
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	57
Max. products per 16A B Breaker	29

### LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

## PHYSICAL DATA

Nominal Product Length (mm)	75
Nominal Product Diameter (mm)	45
Weight (kg)	0.021

## PACKAGING

Product EAN number	5410288296296
Packaging single length / height (cm)	5.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	9.5
DUN14 (inner)	15410288296293
Units per outer package	6
Packaging outer length / height (cm)	15.7
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	10.5

## SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

# SYLVANIA

ToLEDo Ball V7 806LM 827 B22 SL  
0029629

## Energy label



0029629




**7**  
kWh/1000h



2019/2015



0029629



**7**  
kWh/1000h



2019/2015