



UFH-0505CDN10: 10-Group manifold composite, district heating NUON and ENECO



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Energy/district heating, Utility

Technical characteristics

| | | | |
|---------------------------------------|--|--|-----------------------|
| Connection type primary side | 2-pipe | Outer pipe diameter primary connection | 32 Millimetre |
| Suitable for cooling | ✓ | Medium temperature (continuous) | 10 60 Degrees celsius |
| Material | Plastic | Max. operating pressure | 6 Bar |
| Position primary connection | Atop | Max. number of expansion groups | 0 |
| Primary connection | Internal thread cylindrical BSPP-G (ISO 228-1) | Supply voltage | 230 Volt |
| Nominal diameter primary connection | 3/4 inch (20) | Number of groups secondary | 10 |
| With valves on primary connection | ✓ | Outer pipe diameter secondary | 12 20 Millimetre |
| With mixing valve | ✓ | Flow-through capacity | 0 5 Litre per hour |
| Expandable | ✗ | Min. pressure difference secondary flow/return | 0 Kilo Pascal |
| Multi-zone manifold | ✗ | Width | 165 Millimetre |
| With temperature limit | ✓ | Height | 540 Millimetre |
| With non-return valve | ✓ | Depth | 765 Millimetre |
| With circulation pump | ✓ | | |
| Type of pump (system pump) | AC | | |
| Article compression class | PN 6 | | |
| With controller | ✓ | | |
| Hydraulic balance control | Static | | |
| Volume flow measurement | Analogue | | |
| With thermometer | ✓ | | |
| Temperature measurement supply | Analogue | | |
| Temperature measurement return | Analogue | | |
| With de-aeration | ✓ | | |
| With pressure gauge | ✗ | | |
| Secondary connection | Euroconus standardless | | |
| Nominal diameter secondary connection | 3/4 inch (20) | | |
| Closable groups | ✓ | | |
| With flow-through indicator | ✓ | | |
| With thermal actuator | ✗ | | |
| With wall-mounting bracket | ✓ | | |
| With casing | ✗ | | |

Related products