

Double push button with LED for Niko Home Control, bronze coated

123-52036



This push button allows you to control two groups of roll-down shutters, curtains or sunblinds. It is attached to the wall-mounted printed circuit board via a click mechanism. An LED indicates the position of the roll-down shutter, the curtain or the sunblind. Switch including button. Colour: bronze coated.



Technical data

Double push button with LED for Niko Home Control, bronze coated.

- Function:
 - push buttons for motor control are available in a single-row (three control buttons) or double-row (six control buttons) configuration. They allow the resident to operate the motors of one or two groups of roll-down shutters, sunblinds or awnings integrated in the Niko Home Control installation
 - the specific control buttons on each push button are arranged in groups of three. To mount the push button, press the unit onto a Niko Home Control wall-mounted printed circuit board until it clicks into place. The push button is now secure. The functions of the control buttons can be assigned while programming the installation by linking each function to the unique address of each control button during the addressing phase. This information is then stored in the controller
- Material finishing: polycarbonate (PC) + acrylic-styrene-acrylate (ASA)
- Imprint indication: arrows printed on the top and bottom keys show whether you are raising or lowering the roller shutter or blind. On the middle key(s) a shutter is printed including the favourite button. If you press this key the shutter, sunblinds or blind will go straight to the set position
- Number of lenses: 4
- Lens shape: round
- Lens size: 1.5 x 1.5 mm
- Led colour: amber
- Colour: bronze coated
- Colour RAL (approximately): 080 50 05
- Colour NCS (approximately): NCS S 5005-Y20R
- Surface treatment: coated
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)

- all plastic components are halogen-free
- Input voltage: 26 Vdc
- Dismantling method: pull the central plate off the base
- Impact resistance: after mounting, an impact-resistance of IK06 is guaranteed
- Dimensions (HxWxD): 44.5 mm x 44.5 mm x 8.6 mm
- Marking: CE