



Features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate X-feed that is applicable for three-circuit track systems where the polarity ridge is in the outer side and on the left. Dimensions - 166 x 166 x 33 mm (L x W x H), white (RAL 9010).

Product Overview

Product name	GLOBAL TRAC PULSE X FEED WHITE
Technology	Accessory
Housing	PC Polycarbonate
Light colour	N/A
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532666
Warranty	5 years

Data table

GENERAL DATA

Product name	GLOBAL TRAC PULSE X FEED WHITE
Technology	Accessory
Housing	PC Polycarbonate
Operating temperature range (°C)	0°C...+25°C
Warranty	5 years

OPTICAL DATA

Light colour	N/A
--------------	-----

GLOBAL TRAC PULSE X FEED WHITE XTSC638-3

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	RAL 9010 - Pure white
----------------	-----------------------

IP rating	IP20
-----------	------

IK rating	IK02
-----------	------

Nominal Product Length (mm)	166
-----------------------------	-----

Nominal Product Width (mm)	166
----------------------------	-----

Weight (kg)	0.32
-------------	------

PACKAGING

Single packaging type	Plastic
-----------------------	---------

Product EAN number	6410014532666
--------------------	---------------

Packaging single width (cm)	30.0
-----------------------------	------

Packaging single depth (cm)	0.32
-----------------------------	------

DUN14 (outer)	06410014532666
---------------	----------------

Packaging outer length / height (cm)	40.0
--------------------------------------	------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----