



Features

- Logistics and Industry high bay luminaire with Symmetrical Wide beam optics to provide homogenous light distribution for open space areas, comes complete with 2000mm flying lead and 1000mm suspension cable, aluminium housing, PC diffuser, IP65, IK08, Class I, 4000K, CRI80, 3 step MacAdam ellipse, Sylsmart Connected (SSA) - Sensor version, 13500lm, 72W, 188lm/W, 105.000hrs L80B50 lifespan, 446 x 481 x 102mm (LxWxD) dimensions, 4.29kg weight, RAL7012 Basalt Grey color, -20...+40°C operating temperature range.

Product Overview


Product name	Rocks IP65 13KLM 840 WIDE SSA03H
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	13500
Luminaire efficacy (lm/W)	188
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	75
Photobiological Risk Group	RG1
Total power consumption (W)	72
Electrical protection	Class I

Concord

Rocks IP65 13KLM 840 WIDE SSA03H 2825430

Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5025768254309
Warranty	5 years
Dimming method	DALI-2

Photometry



Technical drawings

