

Data Sheet | Item Number: 706-4069/200-200

System cable; Rockwell 5069; 8 digital outputs; Pluggable connector per DIN 41651; Length: 2 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-4069/200-200>



Color coding acc. to DIN VDE 47100 Cable; OUT 0-7		Connector HE10		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		1	OUT 0.0	0	000
Brown		2	OUT 0.1	1	001
Green		3	OUT 0.2	2	002
Yellow		4	OUT 0.3	3	003
Grey		5	OUT 0.4	9	004
Pink		6	OUT 0.5	10	005
Blue		7	OUT 0.6	11	006
Red		8	OUT 0.7	12	007
Black		9	+24 V	8 + 17	LA0+/LA1+
Violet		10	0 V	7 + 16	LA0-/LA1-

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Electrical data

Inputs/outputs	8 digital outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility

Rockwell

Rockwell Compact Logix	5069 - OB8
------------------------	------------

Connection Data

Color code	per DIN VDE 47100
------------	-------------------

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	10
Connection type	System
Wire cross-section	0.14 mm ²

Connection 2

Connector	Rockwell
Pole number	18
Wire cross-section	0.14 mm ²

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	147 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4066966226270
Customs tariff number	85444290900


Product Classification

UNSPSC	26121629
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads**Documentation****System Description**

WAGO System Wiring, Selection Guide	pdf 533.15 KB	
--	------------------	---