

Data Sheet | Item Number: 706-3140/401-300

System cable; for Schneider Modicon Quantum; 8 analog inputs (voltage); Length: 3 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-3140/401-300>



Color coding acc. to DIN VDE 47100	25 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	IN0+	1	MD+
Brown	2	IN0-	2	MD-
Green	3	IN1+	5	M1+
Yellow	4	IN1-	6	M1-
Grey	5	IN2+	13	M2+
Pink	6	IN2-	12	M2-
Blue	7	IN3+	15	M3+
Red	8	IN3-	16	M3-
Black	9	IN4+	21	M4+
Violet	10	IN4-	22	M4-
Grey-Pink	11	IN5+	25	M5+
Red-Blue	12	IN5-	26	M5-
White-Green	13	IN6+	31	M6+
Brown-Green	14	IN6-	32	M6-
White-Yellow	15	IN7+	35	M7+
Yellow-Brown	16	IN7-	36	M7-
White-Gray	17	nc	nc	nc
Grey-Brown	18	nc	nc	nc
White-Pink	19	nc	nc	nc
Pink-Brown	20	nc	nc	nc
White-Blue	21	nc	nc	nc
Brown-Blue	22	nc	nc	nc
White-Red	23	nc	nc	nc
Brown-Red	24	nc	nc	nc
White-Black	25	nc	nc	nc
Shield		Connected to Sub-D		

Similar to illustration

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Inputs/outputs	8 analog inputs; voltage
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Compatibility

Schneider

Schneider Modicon Quantum	140 ACI 030 00 140 AVI 030 00
---------------------------	----------------------------------

Connection Data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1	
Pluggable connector	D-subminiature female connector
Pole number 1	25
Connection type	System
Wire cross-section	0.25 mm ²

Connection 2

Connector	Schneider 140XTS00200
Pole number	40
Connection type	System
Wire cross-section	0.25 mm ²

Physical data

Cable length	3 m
--------------	-----

Material data

Fire load	0 MJ
Weight	1.1 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143046121

Product Classification

UNSPSC	26121629
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
706-3140/401-300



Documentation

System Description

WAGO System Wiring,
Selection Guide

pdf
533.15 KB

