

Global Trac Pulse

GLOBAL TRAC PULSE 4M BLACK

XTSC6400-2



Product features

- Global Trac Pulse - 3 Circuit Track 16A/400V, circuits can be controlled individually, control 2 Circuit 1A/50V FELV AC, DALI (FELV), DMX, LON, EIB, 1-10 V etc. compatible., aluminum body, suitable for surface mounting, 4000 x 31.5 x 32.5 mm (L x W x H), 3.400 kg, black (RAL 9005).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE 4M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC000101
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014531553

DATA TABLE

General data

Product name	GLOBAL TRAC PULSE 4M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC000101
Warranty	5 years

Optical data

Light colour	N/A
--------------	-----

Electrical data

Dimmable	Yes
----------	-----

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02

Global Trac Pulse GLOBAL TRAC PULSE 4M BLACK XTSC6400-2

Nominal Product Length (mm)	4000
Nominal Product Width (mm)	31.5
Nominal Product Height (mm)	32.5
Cutout Dimensions (W x L in mm or Diameter in mm)	4000
Weight (kg)	3.4

Packaging

Single packaging type	Carton
Product EAN number	6410014531553
Packaging single length / height (cm)	400.0
Packaging single width (cm)	3.15
Packaging single depth (cm)	3.25
DUN14 (outer)	06410014531553
Units per outer package	4
Packaging outer length / height (cm)	400.0
Packaging outer width (cm)	12.8
Packaging outer depth (cm)	3.6

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes