

## GLOBAL TRAC PULSE 4M BLACK XTSC6400-2



### Features

- Global Trac Pulse - 3 Circuit Track 16A/400V, circuits can be controlled individually, control 2 Circuit 1A/50V FELV AC, DALI (FELV), DMX, LON, EIB, 1–10 V etc. compatible., aluminum body, suitable for surface mounting, 4000 x 31.5 x 32.5 mm (L x W x H), 3.400 kg, black (RAL 9005).

### Product Overview

Product name	GLOBAL TRAC PULSE 4M BLACK
Technology	Accessory
Housing	Aluminium
Light colour	N/A
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014531553
Warranty	5 years

### Data table

#### GENERAL DATA

Product name	GLOBAL TRAC PULSE 4M BLACK
Technology	Accessory
Housing	Aluminium
Operating temperature range (°C)	0°C...+25°C
Warranty	5 years

#### OPTICAL DATA

## GLOBAL TRAC PULSE 4M BLACK XTSC6400-2

Light colour	N/A
--------------	-----

### ELECTRICAL DATA

Control gear required	No
-----------------------	----

### PHYSICAL DATA

Housing colour	RAL 9005 - Jet black
----------------	----------------------

IP rating	IP20
-----------	------

IK rating	IK02
-----------	------

Nominal Product Length (mm)	4000
-----------------------------	------

Nominal Product Width (mm)	31.5
----------------------------	------

Weight (kg)	3.4
-------------	-----

### PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	6410014531553
--------------------	---------------

Packaging single width (cm)	3.15
-----------------------------	------

Packaging single depth (cm)	3.25
-----------------------------	------

DUN14 (outer)	06410014531553
---------------	----------------

Packaging outer length / height (cm)	400.0
--------------------------------------	-------

### SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----