




- Features:**
- Switched-mode power supply with TopBoost, enabling secondary-side protection via circuit breakers
 - Natural convection cooling when horizontally mounted
 - Encapsulated for use in control cabinets
 - DC OK contact
 - Suitable for both parallel and series operation
 - Electrically isolated output voltage (SELV) per EN 60950-1/UL 60950-1; PELV per EN 60204

Technical data

Input		Output	
Phases	1 / 2	Nominal output voltage $U_{o\ nom}$	24 VDC (SELV)
Nominal input voltage $U_{i\ nom}$	(1 / 2) x 200 ... 500 VAC	Output voltage range	23 ... 28.5 VDC (adjustable)
Input voltage range	(1 / 2) x 180 ... 550 VAC; 254 ... 780 VDC	Default Setting	DC 24 V
Input voltage derating	-0.5 %/V (< 200 VAC); -0.4 %/V (< 280 VDC)	Nominal output current $I_{o\ nom}$	10 A (24 VDC)
Nominal mains frequency range	44 ... 66 Hz; 0 Hz	Nominal output power	240 W
Input current I_i	$\leq 1.975\ A$ (230 VAC); $\leq 1.36\ A$ (230 VAC)	Deviation	$\leq 1\ \%$
Discharge current	$\leq 1\ mA$	Residual ripple	$\leq 30\ mV$ (peak-to-peak)
Inrush current	$\leq 30\ A$ (NTC)	Current limitation	$1.1 \times I_{o\ nom}$ (typ.)
Power factor correction (PFC)	Passive	Overload behavior	Constant current
Mains failure hold-up time	$\geq 78\ ms$ (400 VAC); $\geq 20\ ms$ (200 VAC)		

Signaling and communication	
Signaling	1 x LED DC OK (green) 1 x DC OK contact (make contact; max. 30 VAC/DC; 1 A)
Operation status indicator	Green LED (U_o)

Efficiency/power losses	
Power loss P_i	$\leq 1.3\ W$; $\leq 27.8\ W$ (230 VAC; nominal load); $\leq 20.3\ W$ (400 VAC; nominal load)
Power loss (max.) $P_{i(max)}$	27.8 W (230 VAC / 24 VDC; 10 A)
Efficiency (typ.)	89 % (230 VAC); 92.5 % (400 VAC)

Circuit protection	
Internal fuse	T 6.3 A / 500 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	Circuit breaker: 6 A, 10 A, 16 A; Tripping characteristic: B or C



Safety and protection		
Isolation voltage (pri.-sec.)		DC 4.242 kV
Isolation voltage (pri.-PE)		DC 2.2 kV
Isolation voltage (sec.-PE)		0.7 kVDC
Protection class		I
Protection type		IP20; per EN 60529
Resistance to reverse feed		≤ 35 VDC
Overvoltage category		II
Pollution degree		2
Transient suppression (primary)		Varistor
Overvoltage protection; secondary		Internal protective circuit ≤ 40 VDC (in the event of a fault)
Short-circuit-protected		Yes
Open-circuit-proof		Yes
Parallel operation		Yes
Series operation		Yes
MTBF		> 500,000 h (per IEC 61709)

Connection data		
Connection type 1		Input/output/signaling
Connection technology		CAGE CLAMP®
WAGO connector		WAGO 721 Series
Solid conductor		0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor		0.08 ... 2.5 mm² / 28 ... 12 AWG
Strip length		8 ... 9 mm / 0.31 ... 0.35 inches

Physical data		
Width		55 mm / 2.165 inches
Height		127 mm / 5 inches
Depth from upper-edge of DIN-rail		146.5 mm / 5.768 inches

Mechanical data		
Mounting type		DIN-35 rail

Material data		
Fire load		0.614 MJ
Weight		830 g

Environmental requirements		
Ambient temperature (operation)		-25 ... +70 °C (device starts at -40 °C (type-tested))
Ambient temperature (storage)		-25 ... +85 °C
Relative humidity		5 ... 96 % (no condensation permissible)
Derating		-2.5 %/K (> 55 °C)
Climatic category		3K3 (per EN 60721)



Standards and specifications	
Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 60950-1 UL 508 DNV SEMI F47

Commercial data	
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 9.0	EC002540
ETIM 8.0	EC002540
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143521420
Customs tariff number	85044083900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates		
General approvals		Declarations of conformity and manufacturer's declarations
  		
Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 508	E255817
UR Underwriters Laboratories Inc.	UL 60950-1	E255815
Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
MFD for SEMI F47 WAGO GmbH & Co. KG	-	-

Approvals for marine applications		
		
Approval	Standard	Certificate Name
DNV DNV Germany GmbH	DNV-CG-0339,Aug.2021	TAA00000KT



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-1638

Download icon

Documentation

Bid Text

787-1638	04.07.2019	xml 7.27 KB	Download icon
787-1638	04.06.2019	docx 21.44 KB	Download icon

Instruction Leaflet

Primär getaktete Stromversorgungen CLASSIC	pdf 159.51 KB	Download icon
--	------------------	---------------

CAD/CAE-Data

CAD data

2D/3D Models 787-1638	Download icon
-----------------------	---------------

CAE data

EPLAN Data Portal 787-1638	Download icon
WSCAD Universe 787-1638	Download icon
ZUKEN Portal 787-1638	Download icon

Engineering-Software

Configuration and Commissioning Software

WAGO Line Length Calculation	1.3.5 09.12.2019	exe 329.50 KB	Download icon
------------------------------	---------------------	------------------	---------------

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker

Item No.: 793-5501
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white

Item No.: 793-501
WMB marking card; as card; not stretchable; plain; snap-on type; white

Item No.: 2009-115
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

1.1.1.2 Marking strip



Item No.: 2009-110
Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white



Item No.: 210-831
Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white



Item No.: 210-832
Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

1.1.2 Mounting adapter

1.1.2.1 DIN-rail adapter



Item No.: 787-897/000-010
Carrier rail adapter made of zinc die-cast; horizontal mounting of 787-16xx (TS35)

1.1.3 Tool

1.1.3.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



Item No.: 210-769
SCREWDRIVER; green