

Data Sheet | Item Number: 706-3057/202-300

System cable; for Schneider TSX; 8 digital outputs for higher voltages; Length: 3 m;

Conductor cross-section: 0.34 mm²

<https://www.wago.com/706-3057/202-300>



Color coding acc. to DIN VDE 47100	Connector WAGO 231 (JA)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	OUT0.0	1	L0
Brown	2	OUT0.1	2	L1
Green	3	OUT0.2	3	L2
Yellow	4	OUT0.3	4	L3
Grey	5	OUT0.4	5	L4
Pink	6	OUT0.5	6	L5
Blue	7	OUT0.6	7	L6
Red	8	OUT0.7	8	L7
Black	9	L	5+10+ 15+20	CO-15
Violet	10	nc	nc	cn
Grey-Pink	11	nc	nc	nc
Red-Blue	12	nc	nc	nc

Similar to illustration

Notes

Note	If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Electrical data

Inputs/outputs	8 digital outputs; for higher voltages
Operating voltage	≤ 250 VAC/VDC
Current per wire (max.)	0.75 A

Compatibility

Schneider	
Schneider TSX	TSX DSY 08S5

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1	
Pluggable connector	WAGO 231 Series
Pole number 1	10
Connection type	System
Wire cross-section	0.34 mm ²

Connection 2

Connector	Schneider TSXBLY01
Pole number	20
Connection type	System
Wire cross-section	0.34 mm ²

Physical data

Cable length	3 m
--------------	-----

Material data

Fire load	0 MJ
Weight	1.1 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143039048

Product Classification

UNSPSC	26121629
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-3057/202-300	↓

Documentation

System Description

WAGO System Wiring,
Selection Guide

pdf
533.15 KB

