

UFH-060505-MD: 5-groups Manifold brass,adjustable,with flow meters



Commercial information

Brass manifold for both housing and utility buildings. It is compact in construction and allows smooth installation. This manifold is equipped with flowmeters and fine regulating valves for each circuit. Outlets are connected to eurocone3/4".

Certificates

Applications

Heating, Cooling, Underfloor Heating



Solutions


Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	0 80 Degrees celsius
Material	Brass	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	0
Primary connection	External thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	5
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✗	Flow-through capacity	0 6 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✗	Width	100 Millimetre
Multi-zone manifold	✗	Height	320 Millimetre
With temperature limit	✗	Depth	310 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 6		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✗		
Temperature measurement supply	None		
Temperature measurement return	None		
With de-aeration	✗		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		

Related products

Product code	GTIN	Description	Image
UFH-CAB-I565	05414764139961	Henco Recessed manifold cabinet RAL9003 internal width 565MM	
UFH-CAB-O615	05414764139961	Henco Surface mount cabinet RAL9003 internal width 615MM	
UFH-CAB-O615Z	05414764139961	Henco Surface mount cabinet backless RAL9003 internal width 615MM	
BE32	05414764139961	Henco Jaws (universal) BE-Profile 32x3	

Product code	GTIN	Description	Image
UFH-M-R	05414764139961	Henco Regulating Valve RP630 3/8" UFH-0605..-MR	
UFH-PGKTA	05414764139961	Henco Pump unit with consistent temperature control	
UFH-BTM0606-M	05414764139961	Henco 1 F ball valve with 1 F swivel nut,washer and thermometer	
UFH-B0606-M	05414764139961	Henco 1 f ball valve with 1 f swivel nut and washer	
UFH-ESK060303-M	05414764139961	Henco 1 F end cap with nut,washer,ball valve and air vent 3/8	
UFH-TM050-M	05414764139961	Henco Thermometer for return with EK connections	
UFH-BS05-M	05414764139961	Henco End cap with washer 3/4	