

Data Sheet | Item Number: 706-2500/201-200

System cable; for Siemens S7-1500; 8 digital outputs; Length: 2 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-2500/201-200>



Color coding acc. to DIN VDE 47100		10 poles flat connector		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		1	OUT0.0	1	0
Brown		2	OUT0.1	2	1
Green		3	OUT0.2	3	2
Yellow		4	OUT0.3	4	3
Grey		5	OUT0.4	5	4
Pink		6	OUT0.5	6	5
Blue		7	OUT0.6	7	6
Red		8	OUT0.7	8	7
Black		9	+24V	9-19	L+
Violet		10	0V	10-20	M

Similar to illustration

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Electrical data

Inputs/outputs	8 digital outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility

Siemens

Siemens S7-1500	6ES7 522-1BF00-0AB0
-----------------	---------------------

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	10
Connection type	System
Wire cross-section	0.14 mm ²

Connection 2

Connector	Siemens 6ES7-592-1BM00-0XB0
Pole number	40
Connection type	System
Wire cross-section	0.14 mm ²

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	1.1 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821893523
Customs tariff number	85444290900

Product Classification

UNSPSC	26121629
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
706-2500/201-200



Documentation

System Description

WAGO System Wiring, Selection Guide	pdf 533.15 KB	
--	------------------	---