



Features

- Logistics and Industry high bay luminaire with Aisle optics to provide necessary illumination for narrow areas, comes complete with 2000mm flying lead and 1000mm suspension cable, aluminium housing, PC diffuser, IP65, IK08, Class I, 4000K, CRI80, 3 step MacAdam ellipse, Zhaga Book 18 Ready, 52300lm, 290W, 180lm/W, 105.000hrs L80B50 lifespan, 446 x 963 x 106mm (LxWxD) dimensions, 10.66kg weight, RAL7012 Basalt Grey color, -30...+50°C operating temperature range.

Product Overview

Product name	Rocks IP65 52KLM 840 AISLE Z18
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4327182
Fixture luminous flux (lm)	52300
Luminaire efficacy (lm/W)	180
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Photobiological Risk Group	RG1
Total power consumption (W)	290
Electrical protection	Class I


Concord

Rocks IP65 52KLM 840 AISLE Z18

2825427

Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5025768254279
Warranty	5 years
Dimming method	DALI-2

Photometry



Technical drawings

