

Features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2225 m, 19.5W, 114lm/W, 3000K, CRI 80, 1-10V dimmable, integral 3 hour maintained emergency, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.

Product Overview


| | |
|--|--|
| Product name | GIOTTO 335 3000K RECESSED 1-10V EMERGENCY |
| Technology | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Mount | Ceiling recessed mounting |
| Environment | Indoor |
| Fixture luminous flux (lm) | 2225 |
| Luminaire efficacy (lm/W) | 114 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Glare control | < 25 |
| Photobiological Risk Group | RG0 |
| Luminous flux (emergency) (lm) | 144 |
| Total power consumption (W) | 19.5 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |

Lumiance

GIOTTO 335 3000K RECESSED 1-10V EMERGENCY 3034819

| | |
|-----------------------|------------------------|
| Control gear mounting | Integrated |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | White |
| IP rating | IP44 |
| IK rating | IK10 |
| Product EAN number | 8711971348191 |
| Warranty | 5 years |
| Colour Code | 830 |

Photometry



Technical drawings

