

## BAP-SK2626: Ball valve with handle Push 26x26



### Commercial information

Brass ball valve with 2 plug-in couplings. Handle has a red coating

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 75 mm    |
| Length     | 155 mm   |
| Width      | 47 mm    |
| Net weight | 0.325 kg |

#### Certificates

#### Applications

Potable water, Heating, Sanitary, Compressed air

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                     |  |                                  |                        |
|-------------------------------------|--|----------------------------------|------------------------|
| Surface protection ball             | None   | Diameter bolt hole               | 26                     |
| Material secondary spindle seal     | Ethylene-propylene diene monomer rubber (EPDM) | Outer pipe diameter connection 1 | 26 Millimetre          |
| Nominal diameter connection 1       | DN 20  | Outer pipe diameter connection 2 | 26 Millimetre          |
| Connection 1                        | Insert (push-fitting)                          | Medium temperature (continuous)  | -10 70 Degrees celsius |
| With coupling connection 1          | ✓  | Wrench width                     | 0 Millimetre           |
| Connection 2                        | Insert (push-fitting)                          | Wrench width union nut           | 0 Millimetre           |
| With coupling connection 2          | ✓  |                                  |                        |
| With drain valve                    | ✗  |                                  |                        |
| With drain possibility (connection) | ✓  |                                  |                        |
| With filter                         | ✗  |                                  |                        |
| With thermometer                    | ✗  |                                  |                        |
| Model                               | Straight                                       |                                  |                        |
| With insulation shell               | ✗  |                                  |                        |
| UL quality mark                     | ✗  |                                  |                        |
| ULC quality mark                    | ✗  |                                  |                        |
| FM quality mark                     | ✗  |                                  |                        |
| LPCB quality mark                   | ✗  |                                  |                        |
| Fire-safe                           | ✗  |                                  |                        |
| Medically clean                     | ✗  |                                  |                        |
| Grease-free                         | ✗  |                                  |                        |
| Full bore                           | ✗  |                                  |                        |
| VdS quality mark                    | ✗  |                                  |                        |
| DVGW quality mark for gas           | ✗  |                                  |                        |
| DVGW quality mark for water         | ✗  |                                  |                        |
| KIWA certified                      | ✗  |                                  |                        |
| Type approval according to BBR/EKS  | ✗  |                                  |                        |