

UFH-0605CD10: 10-groups manif.comp, adjustable with flow meter



Commercial information

Composite manifold for both housing and utility buildings. It is solid in construction and allows smooth installation. The double hollow rooms in the body gives it excellent insulation capacities. This manifold is equipped with flowmeters, control valves for each circuit and it supports high flow rates with little pressure loss. Outlets are connected to eurocone 3/4".

Certificates

Applications

Heating, Cooling, Underfloor Heating



Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	5 55 Degrees celsius
Material	Plastic	Max. operating pressure	4 Bar
Position primary connection	Left	Max. number of expansion groups	0
Primary connection	Internal thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	10
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✓	Flow-through capacity	0 5 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✗	Width	140 Millimetre
Multi-zone manifold	✗	Height	405 Millimetre
With temperature limit	✗	Depth	710 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 4		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✓		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	✓		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		

Related products

Product code	GTIN	Description	Image
UFH-C192071	05414764220713	Henco Maximaal thermostaat incl snoer/stekker	
UFH-AO03-MZ	05414764220713	Henco Automatic air vent,without check valve	
UFH-TM050-M	05414764220713	Henco Thermometer for return with EK connections	