

# ABB EcoSolutions™ – SD200 switch disconnecter

## Safe switching

### Switch disconnecter

The SD200 series has a two-terminal cylindrical hub terminal that enables two conductors to be connected up or a conductor and busbar cross-wiring combination.  
The series is available in a 1 to 4 pole design with current ratings ranging from 16 to 63 A and has disconnecter properties as per DIN EN 60947-3



ABB  
**Eco**  
Solutions™



### End-of-life instructions

Clear instructions for product disassembly and recycling individual parts for re-use. ([LINK](#) to the document)

### Enhanced durability

The SD200 Switch disconnecters withstand more mechanical and electrical operations than the ones indicated in the IEC/EN 60947-3 standard.



### Designed for high recyclability & lower material use

Up to **84,9% recyclability rate**, calculated according to EN 45555.

### Produced in a zero waste to landfill site

All non-hazardous waste is recycled, and we continuously work to minimize waste in our operations.

### Sustainable packaging materials

Packaging is made of **100% recycled cardboard**.



#### Third-party verified Environmental Product Declaration

EPD compliant with ISO 14025 Type III (externally verified), ensuring data accuracy and full transparency on the product's environmental impacts throughout its life cycle ([LINK](#) to the EPD).



#### Low-carbon manufacturing

This product is manufactured in an ABB facility that is powered by renewable energy.

[LEARN MORE](#)