

BAP-FFV3207: Inox ball valve with handle, press x female Ø32 x 1 1/4"



Commercial information

Henco Inox ball valve with handle, press x female Ø32 x 1 1/4"

Basic unit dimensions

Height	97 mm
Length	140 mm
Width	55 mm
Net weight	0.540 kg

Certificates

KIWA SE, KIWA

Applications

Potable water, Heating, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Housing material	Stainless steel	Outer pipe diameter connection 2	32 Millimetre
Material quality	Stainless steel 316 L (1.4404)	Medium temperature (continuous)	-10 70 Degrees celsius
Surface protection housing	None	Length of connection 1	61 Millimetre
Material ball	Stainless steel	Working length connection 1	30 Millimetre
Surface protection ball	None	Length of connection 2	78.5 Millimetre
Material spindle	Stainless steel	Working length connection 2	36.5 Millimetre
Material primary spindle seal	Other	Handgrip length	12.2 Millimetre
Material secondary spindle seal	Other		
Nominal diameter connection 1	1 1/4 inch (32)		
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)		
With coupling connection 1	✘		
Nominal diameter connection 2	DN 20		
Connection 2	Press sleeve		
With coupling connection 2	✘		
Contour code connection 2	TH/BE		
Article compression class	PN 16		
With drain valve	✘		
With drain possibility (connection)	✘		
With filter	✘		
With thermometer	✘		
Model	Straight		
With insulation shell	✘		
UL quality mark	✘		
ULC quality mark	✘		
FM quality mark	✘		
LPCB quality mark	✘		
Fire-safe	✘		
Medically clean	✘		
Grease-free	✘		
Full bore	✓		
VdS quality mark	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✓		
Type approval according to BBR/EKS	✘		