

Global Trac Pro GLOBAL TRAC PRO REC 3M WHITE XTSF4300-3



Product features

- Global Trac Pro - 3 Circuit Track, circuits can be controlled individually, aluminium body, suitable for recessed mounting, 3000 x 56 x 32.5 mm (L x W x H), 2.534 kg, white (RAL 9010).



PRODUCT OVERVIEW

| | |
|---------------------|------------------------------|
| Product name | GLOBAL TRAC PRO REC 3M WHITE |
| Technology | Accessory |
| Housing | Aluminium |
| General application | Retail |
| ETIM Class | EC000101 |
| E-number SE | 7402260 |
| Warranty | 5 years |
| Light colour | N/A |
| Dimmable | No |
| Housing colour | RAL 9010 - Pure white |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 6410014507589 |

DATA TABLE

General data

| | |
|----------------------------------|------------------------------|
| Product name | GLOBAL TRAC PRO REC 3M WHITE |
| Technology | Accessory |
| Housing | Aluminium |
| General application | Retail |
| Operating temperature range (°C) | 0°C...+25°C |
| ETIM Class | EC000101 |
| E-number SE | 7402260 |
| Warranty | 5 years |

Optical data

| | |
|--------------|-----|
| Light colour | N/A |
|--------------|-----|

Electrical data

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Physical data

| | |
|----------------|-----------------------|
| Housing colour | RAL 9010 - Pure white |
|----------------|-----------------------|

Global Trac Pro GLOBAL TRAC PRO REC 3M WHITE XTSF4300-3

| | |
|---|-------|
| IP rating | IP20 |
| IK rating | IK02 |
| Nominal Product Length (mm) | 3000 |
| Nominal Product Width (mm) | 56 |
| Nominal Product Height (mm) | 32.5 |
| Cutout Dimensions (W x L in mm or Diameter in mm) | 3000 |
| Weight (kg) | 2.784 |
| Recessed Depth (mm) | 30 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 6410014507589 |
| Packaging single length / height (cm) | 300.0 |
| Packaging single width (cm) | 5.6 |
| Packaging single depth (cm) | 3.3 |
| DUN14 (outer) | 06410014507589 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 300.0 |
| Packaging outer width (cm) | 5.6 |
| Packaging outer depth (cm) | 3.3 |

Safety data

| | |
|----------------------------------|------|
| Optimal operating condition (°C) | 0-25 |
| Special purpose lamp | No |
| Dry applications use only | Yes |

TECHNICAL DRAWINGS

