

Insulation shell for valve R2..

- only for non-condensing applications
- easy mounting thanks to velcro strip
- can also be mounted/dismounted subsequently



### Type Overview

Type	DN	Suitable for	Weight
EXT-OC-ZRN215	15	R2015-.. (kvs ≤1.6)	0.045 kg
EXT-OC-ZRN215G	15	R2015-.. (kvs ≥2.5)	0.045 kg
EXT-OC-ZRN220	20	R2020-..	0.03 kg
EXT-OC-ZRN225	25	R2025-..	0.03 kg
EXT-OC-ZRN232	32	R2032-..	0.03 kg
EXT-OC-ZRN240	40	R2040-..	0.04 kg
EXT-OC-ZRN250	50	R2050-..	0.05 kg

### Technical data

<b>Functional data</b>	Thermal conductivity	0.035 W/mK
<b>Materials</b>	Used Materials	Polyethylen foam (PE-3015 acc. EN 12667:2001 / EN 12664:2001)

### Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.