




**UFH-0605MDK03-03LPRM:** Pre-mounted 3-groups man. comp, flow meter 0-3L, therm., washer and air v



## Commercial information

### Certificates

### Applications

Heating, Cooling, Underfloor Heating

### Solutions

Building installations, Underfloor heating, Industry, Utility

## Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	0 60 Degrees celsius
Material	Plastic	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	15
Primary connection	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)	Number of groups secondary	3
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✗	Flow-through capacity	0 5 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✓	Width	99 Millimetre
Multi-zone manifold	✗	Height	335 Millimetre
With temperature limit	✗	Depth	268 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 6		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✓		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	✓		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		

## Related products