

Walraven BISOFIX® E13 + 2S

(D0304)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- zinc plated
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I133303008	8	M8/M10	58	69	50	13.3	100
I133303010	10.2	M8/M10	58	69	50	13.3	100
I133303012	12	M8/M10	68	78	50	13.3	100
I133303015	15	M8/M10	68	78	50	13.3	100
I133303018	17.2 - 18	M8/M10	68	78	50	13.3	100
I133303022	21.3 - 22	M8/M10	74	84	50	13.5	100
I133303028	26.9 - 28	M8/M10	83	93	50	13.3	100
I133303035	33.7 - 35	M8/M10	89	99	50	13.3	100
I133303042	42.4	M8/M10	96	111	50	13.3	150
I133303048	48.3	M8/M10	103	118	50	13.3	225
I133303054	54	M8/M10	109	124	50	13.3	225
I133303057	57	M8/M10	109	124	50	13.3	350
I133303060	60.3	M8/M10	119	136	50	13.9	350
I133303064	64	M8/M10	127	143	50	18	350
I133303070	70	M8/M10	127	143	50	16.3	425
I133303076	76.1	M8/M10	136	153	50	16.3	575
I133303089	88.9	M8/M10	151	168	50	17.9	875
I133303102	101.6	M8/M10	161	178	50	16.3	1,000
I133303108	108	M8/M10	168	185	50	16.3	1,075
I133303114	114.3	M8/M10	177	194	50	18.9	1,250
I133303133	133	M8/M10	199	217	100	16.3	1,475
I133303140	139.7	M8/M10	210	227	100	18.2	1,700
I133303160	159 - 160	M8/M10	221	239	100	16.3	1,950
I133303168	168.3	M8/M10	232	249	100	16.3	2,125