



Data Sheet | Item Number: 706-3057/300-100

System cable; for Schneider TSX; 16 digital inputs or outputs; Length: 1 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-3057/300-100>



Color coding acc. to DIN VDE 47100	Interface connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	0.0	1	IN/OUT1
Brown	2	0.1	2	IN/OUT2
Green	3	0.2	3	IN/OUT3
Yellow	4	0.3	4	IN/OUT4
Grey	5	0.4	5	IN/OUT5
Pink	6	0.5	6	IN/OUT6
Blue	7	0.6	7	IN/OUT7
Red	8	0.7	8	IN/OUT8
Black	9	1.0	9	IN/OUT9
Violet	10	1.1	10	IN/OUT10
Grey-Pink	11	1.2	11	IN/OUT11
Red-Blue	12	1.3	12	IN/OUT12
White-Green	13	1.4	13	IN/OUT13
Brown-Green	14	1.5	14	IN/OUT14
White-Yellow	15	1.6	15	IN/OUT15
Yellow-Brown	16	1.7	16	IN/OUT16
White-Grey	17	+24V	17	Alim+
Grey-Brown	18	0V	18	Alim-
White-Pink	19	+24V	19	Alim+
Pink-Brown	20	0V	20	Alim-

Short description:

WAGO's Interface Cables provide fast and easy connection of WAGO I/O Modules equipped with a 20-pole pluggable connector (750-1400, -1402, -1500, -1501, -1502) to the appropriate interface or relay modules (16-channel) featuring a 20-pole pluggable connector. The cables are available in 1-, 2- and 3-meter lengths; each has one 20-pole pluggable connector at both ends.

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Electrical data

Inputs/outputs	16 digital inputs or outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility

Schneider

Schneider Modicon Quantum	140 DDI 364 00 140 DDO 364 00
Schneider TSX	TSX DEY 16FK TSX DEY 32D2K TSX DEY 64D2K TSX DEZ 12D2K TSX DMY 28FK TSX DMY 28RFK TSX DMZ 28DTK TSX DMZ 64DTK TSX DSY 32T2K TSX DSY 64T2K

WAGO

WAGO I/O System 750	750-1400 750-1500 750-1502
---------------------	----------------------------------

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	20
Connection type	System
Wire cross-section	0.14 mm ²

Connection 2

Connector	Pluggable connector per DIN 41651; female connector
Pole number	20
Connection type	System
Wire cross-section	0.14 mm ²

Physical data

Cable length	1 m
--------------	-----

Material data

Fire load	0 MJ
Weight	93 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

Product Group	30 (WAGO France)
PU (SPU)	1 pcs
Packaging type	not specified
Country of origin	FR
GTIN	4045454873752
Customs tariff number	85444290900

Product Classification

UNSPSC	26121604
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance			↓
706-3057/300-100			

Documentation

Bid Text			
706-3057/300-100	19.02.2019	xml 3.41 KB	↓
706-3057/300-100	26.11.2018	docx 14.74 KB	↓

Application Notes

Application note, other			
		pdf 2174.17 KB	↓

CAD/CAE-Data

CAE data

WSCAD Universe
706-3057/300-100



1 Compatible Products

1.1 Optional Accessories

1.1.1 Interface module

1.1.1.1 Interface module



[Item No.: 704-2004](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 1-wire connection; in mounting carrier



[Item No.: 704-2024](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



[Item No.: 704-2044](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



[Item No.: 704-2054](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 3-wire connection; in mounting carrier



[Item No.: 704-5004](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



[Item No.: 704-5014](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; without relay; in mounting carrier; 2,50 mm²



[Item No.: 704-5034](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; PCB terminal blocks; with output fuse; in mounting carrier; 2,50 mm²



[Item No.: 704-5024](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



[Item No.: 704-5044](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; with manual operation; in mounting carrier; 2,50 mm²



[Item No.: 704-5054](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



[Item No.: 704-5074](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



[Item No.: 704-5064](#)

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 2 changeover contacts; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



[Item No.: 289-614](#)

Interface module; Pluggable connector per DIN 41651; 20-pole; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²