

Walraven BISOFIX® E13 + Bifix® G2

(D0306)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load
Reference letter	G	H	W	L	Is	Fo,z
Unit description		mm	mm	mm	mm	N
I133008008	M8/M10	62	80	50	13.3	100
I133008010	M8/M10	62	80	50	13.3	100
I133008012	M8/M10	62	80	50	13.3	100
I133008015	M8/M10	66	84	50	13.3	100
I133008018	M8/M10	66	84	50	13.3	100
I133008022	M8/M10	73	91	50	13.5	100
I133008028	M8/M10	79	97	50	13.3	100
I133008035	M8/M10	86	104	50	13.3	100
I133008042	M8/M10	92	110	50	13.3	150
I133008048	M8/M10	100	118	50	13.3	225
I133008054	M8/M10	107	125	50	13.3	225
I133008057	M8/M10	107	125	50	13.3	350
I133008060	M8/M10	115	134	50	13.9	350
I133008064	M8/M10	129	148	50	18	350
I133008070	M8/M10	129	148	50	16.3	425
I133008076	M8/M10	137	155	50	16.3	575
I133008089	M8/M10	154	172	50	17.9	875
I133008102	M8/M10	162	181	50	16.3	1,000
I133008108	M8/M10	162	181	50	16.3	1,075
I133008114	M8/M10	183	201	50	18.9	1,250
I133008133	M8/M10	195	217	100	16.3	1,475
I133008140	M8/M10	208	229	100	18.2	1,700
I133008160	M8/M10	227	248	100	16.3	1,950
I133008168	M8/M10	227	248	100	16.3	2,125