

# Product Environmental Profile





Representative	P3-100/V/SVB-SW/N (Y7-027009)
product	Product Category: Disconnectors
Description of the product	Eaton's Switch Disconnector are designed to turn off all or part of an installation by disconnecting the installation or part of the installation of all electrical energy or earth, for safety reasons. These switch disconnectors have total 3+N poles, rear mount and with STOP Function.
Homogeneous Environmental Families Covered	The PEP concerns following product offerings from Eaton Moeller® series P3 switch disconnector, P3-100/V/SVB-SW/N (Y7-027009) (Reference) as mentioned below: P3-63/V/SVB-SW/N (Y7-017517); P3-80/V/SVB-SW/N (Y7-400971); P3-63/V/SVB/N (Y7-015144); P3-100/V/SVB/N (Y7-024636); P3-80/V/SVB/N (Y7-400966) *[The product market is spread globally. Different scenarios are studied considering distribution in UK and outside Europe and separate extrapolation factors are given in this PEP considering Europe market as reference]
Functional unit	"Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V, and rated current 100A, ensuring isolation characterised by a rated voltage 6000V AC, and with IP Rating of IP65, according to the appropriate use scenario, and during the reference service life of the product of 20 years."
Company information	Eaton Production International GmbH, Claylands Avenue, Dukeries Industrial Estate, Worksop, United Kingdom, S81 7DJ Email: <u>productstewardship-es@eaton.com</u>

Constituent Materials			
Reference product mass	6.53E-01 kg (With packaging)		
Category PEP Material	Materials	Mass (kg)	Percentage (%)
Metals	Stainless Steel	2.03E-01	31.0%
Plastics	Polyamide66GF30	1.75E-01	26.8%
Plastics	Polyamide6	8.52E-02	13.0%
Metals	Brass	5.44E-02	8.3%
Others	Carton	4.78E-02	7.3%
Metals	Copper	2.44E-02	3.7%
Plastics	Polyamide66	1.49E-02	2.3%
Plastics	Phenolic Resin	1.33E-02	2.0%
Metals	Steel Wire Rod	9.52E-03	1.5%
Metals	Silver	8.32E-03	1.3%
Plastics	Polybutylene terephthalate	6.70E-03	1.0%
Others	Paper	5.00E-03	0.8%
Plastics	Polycarbonate	4.28E-03	0.7%
Plastics	Nitrile Butadiene Rubber	7.88E-04	0.1%
Others	Miscellaneous	6.98E-04	<0.1%
	Total	6.53E-01	100.0%

# Substance Assessment

The representative product is compliant with the EU-RoHS Directive (2011/65/EU) without any exemption and the product doesn't contain any substance listed as Substance-of-Very-High-Concern (SVHC) on the Candidate List of the EU-REACH Regulation (1907/2006/EC).

Additional Envir	onmental Information
Manufacturing	The reference product is assembled at an Eaton plant in United Kingdom, holding management system
Manufacturing	certifications according to ISO 14001 standards.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize
Distribution	transport efficiency.
Installation	The installation process does not require any energy consumption and there is no waste other than
installation	the obsolete product packaging generated during this step.
Use	The product requires energy consumption during operation.
	The recyclability rate of the overall product is 89% if it is properly dismantled prior to shredding. The
End of life	rate is calculated based on "ECO'DEEE recyclability and recoverability calculation method" (version V1,
	20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

## **Environmental Impacts**

The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e., "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life.

System modelling was carried out using the commercial LCA software EIME v6.1.3 with database version CODDE-2023-02.

Indicators Set: PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0

Manufacturing Phase	The product is assembled as well as packed at Eaton Production International GmbH, United Kingdom, plant. Energy model used: United Kingdom
Distribution Phase	Distribution of the product in its packaging from Eaton's last logistics platform to the installation place is considered in Europe.
Installation Phase	Product is installed in Europe. Treatment of packaging waste is considered in this phase as per country specific statistics given in PSR. Energy model used: Europe
Use Phase	Reference lifetime: 20 Years Usage profile: The product has power loss of 7.5 W per pole at full load condition. For industrial and commercial applications under low voltage scenario considering 50% of the loading rate and 30% use time rate, total losses are 394.2 kWh over the 20 years. Product do not require any maintenance/replacement during useful life. Energy Model Used: Europe
End of life Phase	Product disposed with WEEE guidelines. Energy model used: Europe
Module-D	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the system and are not to be included in the life cycle totals.

#### **Environmental Impact Indicators: Mandatory**

Mandatory environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 – Operation Energy Use	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Climate change - total (GWP)	kg CO₂ eq.	1.46E+02	5.90E+00	1.56E-01	1.50E-01	1.39E+02	9.30E-01	-3.28E+00
Climate change - fossil fuels (GWP-f)	kg CO₂ eq.	1.46E+02	5.93E+00	1.56E-01	6.32E-02	1.39E+02	9.20E-01	-3.33E+00
Climate change - biogenics (GWP-b)	kg CO₂ eq.	3.19E-01	-3.31E-02	0.00E+00	8.64E-02	2.56E-01	1.04E-02	4.85E-02
Climate change - land use and land	kg CO₂ eq.	6.94E-06	6.58E-06	0.00E+00	0.00E+00	0.00E+00	3.61E-07	-5.44E-06

Mandatory environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 – Operation Energy Use	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
use transformation (GWP-lu)								
Ozone depletion (ODP)	kg eq. CFC- 11	1.53E-06	6 8.34E-07 2.39E-10		1.90E-09	6.73E-07	1.54E-08	-4.54E-07
Acidification (AP)	mole of H⁺ eq.	7.68E-01	4.99E-02	9.87E-04	2.05E-04	7.12E-01	4.99E-03	-2.58E-02
Freshwater eutrophication (EP- fw)	kg P eq.	1.23E-03	3.96E-04	5.84E-08	7.33E-07	3.66E-04	4.65E-04	-4.61E-05
Marine aquatic eutrophication (EP- m)	kg of N eq.	9.39E-02	5.94E-03	4.62E-04	8.30E-05	8.67E-02	7.37E-04	-3.32E-03
Terrestrial eutrophication (EP- t)	mole of N eq.	1.46E+00	5.64E-02	5.07E-03	5.70E-04	1.39E+00	8.74E-03	-2.62E-02
Photochemical ozone formation (POCP)	kg of NMVOC eq.	2.95E-01	1.81E-02	1.28E-03	1.37E-04	2.73E-01	2.58E-03	-8.83E-03
Depletion of abiotic resources - elements (ADP-e)	kg eq. Sb	1.18E-02	1.17E-02	6.13E-09	4.33E-09	4.92E-05	1.46E-05	-5.97E-03
Depletion of abiotic resources - fossil fuels (ADP-f)	MJ	3.68E+03	1.20E+02	2.17E+00	5.98E-01	3.51E+03	4.75E+01	-5.47E+01
Water scarcity (WDP)	m <sup>3</sup> eq. deprivation worldwide	1.40E+01	2.78E+00	5.92E-04	1.30E-02	1.06E+01	5.12E-01	-1.63E+00

# Inventory Flow Indicators: Mandatory

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 – Operation Energy Use	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	9.35E+02	6.14E+00	2.90E-03	2.00E-01	9.28E+02	8.58E-01	-1.07E+00
Use of renewable primary energy resources used as raw materials	MJ	1.84E+00	1.84E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-7.71E-01

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 – Operation Energy Use	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	9.37E+02	7.98E+00	2.90E-03	2.00E-01	9.28E+02	8.58E-01	-1.84E+00
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	3.67E+03	1.12E+02	2.17E+00	5.98E-01	3.51E+03	4.75E+01	-4.81E+01
Use of non-renewable primary energy resources used as raw materials	MJ	8.60E+00	8.60E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-6.58E+00
Total use of non- renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	3.68E+03	1.20E+02	2.17E+00	5.98E-01	3.51E+03	4.75E+01	-5.47E+01
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	m <sup>3</sup>	3.28E-01	6.51E-02	1.38E-05	5.47E-04	2.50E-01	1.19E-02	-3.78E-02
Hazardous waste disposed of	kg	6.18E+01	5.51E+01	0.00E+00	3.20E-03	6.09E+00	6.06E-01	-2.97E+01
Non-hazardous waste disposed of	kg	2.52E+01	1.51E+00	5.47E-03	2.09E-02	2.35E+01	1.91E-01	-5.13E-01
Radioactive waste disposed of	kg	6.07E-03	6.01E-04	3.89E-06	3.45E-06	5.38E-03	7.78E-05	-2.88E-04
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	8.40E-01	2.59E-01	0.00E+00	4.37E-02	0.00E+00	5.38E-01	0.00E+00
Materials for energy recovery	kg	8.82E-03	4.61E-05	0.00E+00	4.94E-03	0.00E+00	3.83E-03	0.00E+00
Exported energy	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the product	kg of C.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	kg of C.	4.40E-02	4.40E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

# **Environmental Impact Indicators: Optional**

Optional Environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 – Operation Energy Use	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Emission of fine particles	incidence of diseases	6.43E-06	6.60E-07	8.02E-09	1.19E-09	5.73E-06	3.23E-08	-3.62E-07
Ionizing radiation, human health	kBq U <sup>235</sup> eq.	2.33E+02	2.79E+01	3.79E-04	4.99E+00	2.00E+02	2.22E-01	-1.48E+01
Ecotoxicity, fresh water	CTUe	2.82E+03	2.55E+03	1.02E-01	8.27E-01	2.62E+02	6.12E+00	-2.26E+03
Human toxicity, cancer effects	CTUh	3.88E-06	3.86E-06	2.74E-12	5.74E-09	1.75E-08	5.13E-10	-2.15E-06
Human toxicity, non- cancer effects	CTUh	1.05E-06	5.91E-07	5.30E-11	1.82E-10	4.17E-07	3.88E-08	-3.06E-07
Impacts related to land use/soil quality	-	5.80E+00	8.26E-01	0.00E+00	1.61E-04	3.85E+00	1.12E+00	-1.52E-02
Total use of primary energy during the life cycle	MJ	4.62E+03	1.28E+02	2.18E+00	7.98E-01	4.44E+03	4.83E+01	-5.65E+01

To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-Multiplying Factors for all phases (EU region):

Part No.	Description	Extrapolation Factors for Manufacturing, distribution, installation, End of Life and Module-D phase	Extrapolation Factor for Use Phase
Y7-027009 (Reference)	P3-100/V/SVB-SW/N	1.00	1.00
Y7-017517	P3-63/V/SVB-SW/N	1.00	0.60
Y7-400971	P3-80/V/SVB-SW/N	1.00	1.00
Y7-015144	P3-63/V/SVB/N	1.00	0.60
Y7-024636	P3-100/V/SVB/N	1.00	1.00
Y7-400966	P3-80/V/SVB/N	1.00	1.00

# Factors for Manufacturing, Distribution, Installation, End of Life and Module-D phase for different geographical regions

Product	Geographical regions	Phases	GWP	GWP- f	GWP- b	GWP- lu	ODP	AP	EP-fw	EP- m	EP-t	РОСР	ADP- e	ADP- f	WDP
	Europe (Reference)	All Phase							1.00						
Y7-027009	United	Manufacturing, EoL, Module-D							1.00						
(Reference)	Kingdom	Distribution							0.29						
		Installation	0.99	0.98	1.00	1.00	1.00	0.97	1.00	0.99	1.01	0.98	0.93	0.96	0.99
		Manufacturing							1						
PEP ecopa	PEP ecopassport <sup>®</sup> n° EATO-00162-V01.01-EN								Page	6   7					

Product	Geographical regions	Phases	GWP	GWP- f	GWP- b	GWP- lu	ODP	AP	EP-fw	EP- m	EP-t	РОСР	ADP- e	ADP- f	WDP
	Qutsido	Distribution	1.34	1.34	1.00	1.00	1.14	7.00	1.23	3.56	3.55	3.63	1.22	1.22	1.17
	Europo	Installation	0.68	0.30	0.96	1.00	0.35	0.56	0.02	0.34	0.65	0.58	0.31	0.58	0.06
	Europe	End of Life	0.34	0.34	0.09	0.001	1.93	0.46	0.001	0.80	0.87	0.66	0.001	0.12	0.06

## Factors for use phase for different geographical regions

Product	Geographical regions	ADP- e (kg SB eq.)	ADP- -f (MJ)	AP (mol H⁺ eq.)	Ep-f (kg P eq.)	Ep-m (kg N eq.)	Ep-t (mol N eq.)	GWP (kg CO <sub>2</sub> eq.)	GWP- b (kg CO <sub>2</sub> eq.)	GWP- f (kg CO <sub>2</sub> eq.)	GWP- lu (kg CO2 eq.)	ODP (kg CFC- 11 eq.)	POCP (kg NMVOC eq.)	WDP (m³ eq.)
Y7-199914 (Reference)	Europe (Reference)	1.00												
	Germany	1.09	0.86	1.50	0.54	1.34	1.39	1.07	0.73	1.07	1.00	1.43	1.35	1.28
	UK	0.79	0.75	0.67	0.79	0.69	1.17	0.71	1.19	0.71	1.00	0.82	0.61	0.66
	Austria	1.65	0.23	0.43	0.01	0.40	0.63	0.37	0.65	0.37	1.00	0.37	0.36	1.10
	Netherlands	0.79	0.77	0.80	0.18	0.95	0.98	1.14	1.33	1.14	1.00	1.01	0.94	0.92
	India	0.60	2.47	5.87	0.16	5.13	3.64	3.93	0.25	3.94	1.00	4.74	5.44	2.69
	Czech Republic	0.45	1.66	2.35	1.77	2.05	1.77	1.59	0.44	1.59	1.00	2.02	2.12	1.20
	Finland	0.73	0.86	0.91	1.59	0.68	1.42	0.39	0.61	0.39	1.00	0.71	0.56	0.54
	Denmark	0.83	0.35	1.16	0.04	0.98	1.66	0.56	0.90	0.56	1.00	1.30	0.86	0.58

#### Disclaimer

This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

Registration Number	EATO-00162-V01.01-EN	Drafting rules	PCR-ed4-EN-2021 09 06						
Verifier accreditation Number	VH53	Supplemented by	PSR-0005-ed3.1-EN-2023 08 12						
Date of issue	07-2024	Information and reference documents	www.pep-ecopassport.org						
		Validity period	5 years						
Independent verification of the declaration and data, in compliance with ISO 14025: 2006									
Internal	X								
The PCR review was conduct									
(DDemain)									
PEPs are compliant with XP									
The components of the prese									
other program.	PASS								
Document complies with ISC	Font								
Type III environmental decla									