


Data Sheet | Item Number: 706-7753/301-200

System cable; for WAGO I/O-SYSTEM, 753 Series; 2 x 16 digital inputs or outputs;

Length: 2 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-7753/301-200>



Color coding acc. to DIN VDE 47100	Connector HE10 20 pts		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	0.0	1A	ED1/SD1
Brown	2	0.1	5A	ED2/SD2
Green	3	0.2	2A	ED3/SD3
Yellow	4	0.3	6A	ED4/SD4
Grey	5	0.4	3A	ED5/SD5
Pink	6	0.5	7A	ED6/SD6
Blue	7	0.6	4A	ED7/SD7
Red	8	0.7	8A	ED8/SD8
Black	9	1.0	1B	ED9/SD9
Violet	10	1.1	5B	ED10/SD10
Grey-Pink	11	1.2	2B	ED11/SD11
Red-Blue	12	1.3	6B	ED12/SD12
White-Green	13	1.4	3B	ED13/SD13
Brown-Green	14	1.5	7B	ED14/SD14
White-Yellow	15	1.6	4B	ED15/SD15
Yellow-Brown	16	1.7	8B	ED16/SD16
White-Grey	17	nc	nc	nc
Grey-Brown	18	nc	nc	nc
White-Pink	19	nc	nc	nc
Pink-Brown	20	nc	nc	nc

Short description:

WAGO's interface cables provide fast and easy connection of WAGO I/O Modules equipped with a pluggable connector (e.g., 753-430, -431, -530) to the appropriate interface or relay modules featuring a 20-pole female connector.

For example, these cables can connect two WAGO I/O Modules to one relay output module (16-channel).

Notes

Note	Observe the maximum operating temperature of the WAGO I/O modules used.
------	---

Electrical data

Inputs/outputs	16 digital inputs or outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility

WAGO

WAGO I/O System 753	753-430 (x2)
	753-431 (x2)
	753-530 (x2)

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	8
Connection type	System
Wire cross-section	0.14 mm ²

Connection 2

Connector	WAGO 753-110
Pole number	8
Connection type	System
Wire cross-section	0.14 mm ²

Connection 3

Connector	WAGO 753-110
Pole number	20
Connection type	System
Wire cross-section	0.14 mm ²

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	196 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

Product Group	30 (WAGO France)
PU (SPU)	1 pcs
Packaging type	not specified
Country of origin	QU
GTIN	4045454874131
Customs tariff number	85444290900

Product Classification

UNSPSC	26121604
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-7753/301-200	↓
--	-------------------

Documentation

Bid Text

706-7753/301-200	19.02.2019	xml 3.62 KB	↓
706-7753/301-200	26.11.2018	docx 15.20 KB	↓

CAD/CAE-Data

CAE data

WSCAD Universe 706-7753/301-200	↓
------------------------------------	-------------------

1 Compatible Products

1.1 Optional Accessories

1.1.1 Interface module

1.1.1.1 Interface module



Item No.: 704-2004

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 1-wire connection; in mounting carrier



Item No.: 704-2024

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



Item No.: 704-2044

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



Item No.: 704-2054

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 3-wire connection; in mounting carrier



Item No.: 704-5004

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 704-5014

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; without relay; in mounting carrier; 2,50 mm²



Item No.: 704-5034

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; PCB terminal blocks; with output fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5024

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 704-5044

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; with manual operation; in mounting carrier; 2,50 mm²



Item No.: 704-5054

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5074

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5064

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 2 changeover contacts; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 289-614

Interface module; Pluggable connector per DIN 41651; 20-pole; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²