


28PK-04: Clip for 28PK-2PK1604, 28PK-6PK1604, 28PK-13PK160416



Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

Basic unit dimensions

Height	18 mm
Length	195 mm
Width	38 mm
Net weight	0.067 kg

Certificates

Applications

Potable water, Heating, Compressed air, Cooling, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Inlay	None	Outer pipe diameter	16 16 Millimetre
Connection facility	Hole	Permitted work load	15 Newton
Connection size, connection facility	None		
Flexible connection facility	✗		
Lock facility	Integrated		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Suitable for steel tube	✗		
Suitable for thin-walled pipe	✗		
Suitable for stainless steel tube	✗		
Suitable for copper tube	✗		
Suitable for aluminium tube	✗		
Suitable for cast iron pipe	✗		
Suitable for plastic tube	✓		
Suitable for pipe coil	✗		
KIWA certified	✗		