


Walraven BISOFIX® PIR40 + 2S

(D0372)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	VVS Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter		D	G	H	W	L	Is	Fa,z
Unit description		mm		mm	mm	mm	mm	N
I403303140	18002494	139.7	M8/M10	253	271	100	40	1,730
I403303012	18002412	12	M8/M10	119	136	75	40	300
I403303015	18002416	15 - 16	M8/M10	119	136	75	40	320
I403303018	18002418	17.2 - 18	M8/M10	127	143	75	40	340
I403303020		20	M8/M10	127	143	75	40	340
I403303022	18002422	21.3 - 22	M8/M10	127	143	75	40	350
I403303028	18002428	26.9 - 28	M8/M10	136	153	75	40	350
I403303032		32	M8/M10	136	153	75	40	370
I403303034	18002435	33.7 - 35	M8/M10	136	153	75	40	370
I403303040	18002440	40	M8/M10	151	168	75	40	400
I403303042	18002442	42.4	M8/M10	151	168	75	40	410
I403303048	18002448	48.3	M8/M10	161	178	75	40	430
I403303054	18002454	54	M8/M10	161	178	75	40	440
I403303057	18002457	56 - 57	M8/M10	161	178	75	40	460
I403303060	18002460	60.3	M8/M10	168	185	75	40	470
I403303064	18002464	64	M8/M10	168	185	75	40	490
I403303070	18002470	70	M8/M10	177	194	75	40	510
I403303076	18002476	76.1	M8/M10	186	203	75	40	530
I403303102	18002492	101.6	M8/M10	210	227	100	40	650
I403303108	18002490	108	M8/M10	221	239	100	40	690
I403303114	18002491	114.3	M8/M10	221	239	100	40	1,560
I403303133	18002493	133	M8/M10	243	260	100	40	1,670