

Data Sheet | Item Number: 706-100/537-1000

Connection cable; 37-pole; with solder pin; Male connector; open-ended; Length: 10 m;
Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-100/537-1000>



Similar to illustration



Similar to illustration

Color coding acc. to DIN VDE 47100		37 pole male Sub-D connector	
		Pole number	
White		1	
Brown		2	
Green		3	
Yellow		4	
Grey		5	
Pink		6	
Blue		7	
Red		8	
Black		9	
Violet		10	
Grey-Pink		11	
Red-Blue		12	
White-Green		13	
Brown-Green		14	
White-Yellow		15	
Yellow-Green		16	
White-Grey		17	
Grey-Brown		18	
White-White		19	
Pink-Brown		20	
White-Blue		21	
Brown-Black		22	
White-Red		23	
Brown-Red		24	
White-Black		25	
Brown-Black		26	
Grey-Green		27	
Yellow-Grey		28	
Pink-Green		29	
Yellow-Pink		30	
Green-Blue		31	
Yellow-Blue		32	
Green-Red		33	
Yellow-Red		34	
Green-Black		35	
Yellow-Black		36	
Grey-Blue		37	
Shield		Connected to Sub-D	

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Connection Data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Pluggable connector	D-subminiature male connector
Pole number 1	37
Connection type	System
Wire cross-section	0.25 mm²



Connection 2	
Connector	open-ended
Connection type	open-ended
Wire cross-section	0.25 mm²

Physical data	
Cable length	10 m

Material data	
Weight	2353 g

Environmental requirements	
Ambient temperature (operation)	-20 ... +50 °C

Commercial data	
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4066966698077
Customs tariff number	85444290900

Product Classification	
UNSPSC	26121604
ETIM 9.0	EC001855
ETIM 10.0	EC001855
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
706-100/537-1000

↓