




## 28PK-04: Clip for 28PK-2PK1604, 28PK-6PK1604, 28PK-13PK1604 16



### Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)\*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

#### Basic unit dimensions

Height	18 mm
Length	195 mm
Width	38 mm
Net weight	0.067 kg

#### Certificates

#### Applications

Potable water, Heating, Compressed air, Cooling, Demi Water, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Inlay	None	Outer pipe diameter	16 16 Millimetre
Connection facility	Hole	Permitted work load	15 Newton
Connection size, connection facility	None		
Flexible connection facility	✘		
Lock facility	Integrated		
FM quality mark	✘		
UL quality mark	✘		
ULC quality mark	✘		
LPCB quality mark	✘		
Suitable for steel tube	✘		
Suitable for thin-walled pipe	✘		
Suitable for stainless steel tube	✘		
Suitable for copper tube	✘		
Suitable for aluminium tube	✘		
Suitable for cast iron pipe	✘		
Suitable for plastic tube	✓		
Suitable for pipe coil	✘		
KIWA certified	✘		