



Features

• OPTIX SURFACE 1200 MPO D/I HO 4000K is a high efficacy low glare suspended LED Linear luminaire with Micro Prismatic diffuser, with direct/indirect light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, Constant Current driver, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 5770lm luminous flux, 60/40 D/I light distribution ratio, 44W power consumption, 131lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 3000 cd/m2, lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.


Product Overview

Product name	OPTIX SURFACE 1200 MPO D/I HO 4000K
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture luminous flux (lm)	5770
Luminaire efficacy (lm/W)	131
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 18
Photobiological Risk Group	RG1
Total power consumption (W)	44
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)


OPTIX SURFACE 1200 MPO D/I HO 4000K
2021660

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216604
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX SURFACE 1200 MPO D/I HO 4000K
--------------	-------------------------------------

OPTIX SURFACE 1200 MPO D/I HO 4000K 2021660

Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	5770
Luminaire efficacy (lm/W)	131
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 18
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	44
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	15
Inrush Duration (µs)	100
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	30

OPTIX SURFACE 1200 MPO D/I HO 4000K 2021660

Max. products per 20A B Breaker	60
---------------------------------	----

LIFETIME DATA

Lifespan L70 B50	238000
------------------	--------

Lifespan L80 B20	130000
------------------	--------

Lifespan L90 B10	58000
------------------	-------

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
----------------	----------------------------------

IP rating	IP20
-----------	------

IK rating	IK07
-----------	------

Diffuser material	PMMA Acrylic
-------------------	--------------

Nominal Product Length (mm)	1200
-----------------------------	------

Nominal Product Width (mm)	200
----------------------------	-----

Weight (kg)	4.6
-------------	-----

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5025768216604
--------------------	---------------

Packaging single width (cm)	22.5
-----------------------------	------

Packaging single depth (cm)	6.8
-----------------------------	-----

DUN14 (outer)	05025768216604
---------------	----------------

Packaging outer length / height (cm)	122.0
--------------------------------------	-------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----