Data Sheet | Item Number: 770-523

Shield connecting plate; 3-pole; for sockets and plugs; silver-colored

https://www.wago.com/770-523



Color: silver-colored

Shield termination *WINSTA*® MIDI 3-pole

When using the shield termination from the *WINSTA*® MIDI product line, zero-defect installation is guaranteed. An extensive range of accessories complements the WINSTA® product line from WAGO. *WINSTA*® MIDI with Push-in CAGE CLAMP® spring pressure connection technology is used in can be found in a variety of projects you can use for quick, easy, flexible, and secure installation.

Lower costs through fast commissioning and elimination of service expenses – solutions from *WINSTA*® MIDI

The WINSTA® Pluggable Connection System is perfectly tailored to the strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, more reliable, and error-free. Use of this pre-assembled system reduces time spent on assembly and installation errors at the construction site. Take advantage of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with protection against mismating from WAGO.

- pre-assembled versions
- quick replacement of defective units during ongoing operation

Notes

General safety information	**NOTICE: Observe installation and safety instructions!** • Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden! • Nicht unter Spannung/Last installieren! • Nur für bestimmungsgemäßen Gebrauch einsetzen! • Nationale Vorschriften/Normen/Richtlinien beachten! • Technische Daten der Produkte beachten! • Auf die richtige Polbelegung achten! • Keine beschädigten/verschmutzten Komponenten verwenden! • Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten! • Leiter bis zum Anschlag einführen! • Nur mit Verriegelungsklinke und Zugentlastung verwenden! • Originalzubehör verwenden! **To be sold only with installation instructions!**

Connection Data

Connection 1

Pole number	3

Physical data

Width	25.6 mm / 1.004 inches
Height	6.95 mm / 0.274 inches
Depth	44.8 mm / 1.764 inches

Mechanical data

Suitable	for socket and plug

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Flammability class per UL94	V0
Fire load	0 MJ
Weight	2.4 g
Material	Copper (SE Cu); special tin coating

Environmental requirements

Processing temperature	-5 … +40 °C
Continuous operating temperature	-35 … +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454662684
Customs tariff number	85366990990

Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Continued on next page

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-523

Documentation

Bid Text

770-523	19.02.2019	xml 2.60 KB
770-523	11.03.2015	doc 21.50 KB

CAD/CAE-Data

CAD data

2D/3D Models 770-523

CAE data

WSCAD Universe 770-523