


## Walraven BISOFIX® PIR30 + 2S

(D0362)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm}$  =  $80\text{kg/m}^3$
- PIR density for  $D > 110\text{mm}$  =  $120\text{kg/m}^3$
- thermal conductivity  $\lambda$  (approx. value):  $0.30\text{ W/(mK)}$
- clamp: zinc plated
- temperature range  $-45\text{ }^\circ\text{C} - +105\text{ }^\circ\text{C}$

| Product Number   | Outside<br>Pipe<br>Diameter | Connection<br>Thread | Total<br>Height | Total<br>Width | Total<br>Length | Insulation<br>Thickness | Maximum<br>Allowed<br>Load<br>Faz |
|------------------|-----------------------------|----------------------|-----------------|----------------|-----------------|-------------------------|-----------------------------------|
| Reference Letter | D                           | G                    | H               | W              | L               | Is                      | Fa,z                              |
| Unit description | mm                          |                      | mm              | mm             | mm              | mm                      | N                                 |
| I303303114       | 114.3                       | M8/M10               | 210             | 227            | 100             | 30                      | 1,370                             |
| I303303018       | 17.2 - 18                   | M8/M10               | 103             | 118            | 75              | 30                      | 190                               |
| I303303022       | 21.3 - 22                   | M8/M10               | 109             | 124            | 75              | 30                      | 230                               |
| I303303028       | 26.9 - 28                   | M8/M10               | 119             | 136            | 75              | 30                      | 300                               |
| I303303034       | 33.7 - 35                   | M8/M10               | 119             | 136            | 75              | 30                      | 320                               |
| I303303042       | 42.4                        | M8/M10               | 127             | 143            | 75              | 30                      | 350                               |
| I303303048       | 48.3                        | M8/M10               | 136             | 153            | 75              | 30                      | 370                               |
| I303303054       | 54                          | M8/M10               | 136             | 153            | 75              | 30                      | 380                               |
| I303303064       | 64                          | M8/M10               | 151             | 168            | 75              | 30                      | 420                               |
| I303303089       | 88.9                        | M8/M10               | 177             | 194            | 75              | 30                      | 500                               |
| I303303012       | 12                          | M8/M10               | 103             | 118            | 75              | 30                      | 130                               |
| I303303015       | 15 - 16                     | M8/M10               | 103             | 118            | 75              | 30                      | 170                               |
| I303303057       | 56 - 57                     | M8/M10               | 136             | 153            | 75              | 30                      | 390                               |
| I303303060       | 60.3                        | M8/M10               | 151             | 168            | 75              | 30                      | 410                               |
| I303303070       | 70                          | M8/M10               | 161             | 178            | 75              | 30                      | 440                               |
| I303303102       | 101.6                       | M8/M10               | 186             | 203            | 100             | 30                      | 550                               |
| I303303108       | 108                         | M8/M10               | 199             | 217            | 100             | 30                      | 620                               |
| I303303140       | 139.7                       | M8/M10               | 232             | 249            | 100             | 30                      | 1,570                             |
| I303303160       | 159 - 160                   | M8/M10               | 253             | 271            | 100             | 30                      | 1,720                             |