

## PLP-P-PK: Galvanised bracket for backplate elbow



### Commercial information

Wall mounted bracket

This 3 mm full steel galvanized bracket can be used for different applications: shower & bath faucets, under sink mounting and robust anchoring behind plaster wall frame[1]work. It has the following specifications:

- Robust steel bracket
- Rigid wall attachment
- Accurate interaxis fixation
- Various depths for concealed mouting
- Free choice of any backplate fitting

#### Basic unit dimensions

Height	35 mm
Length	210 mm
Width	35 mm
Net weight	0.220 kg

#### Certificates

#### Applications

Potable water, Heating, Compressed air, Gas, Sanitary

#### Solutions

Building installations, Industry, Oil & gas, Utility

## Technical characteristics

Inlay	None	Outer pipe diameter	16 32 Millimetre
Connection facility	Other		
Connection size, connection facility	Other		
Flexible connection facility	✘		
Lock facility	Other		
FM quality mark	✘		
UL quality mark	✘		
ULC quality mark	✘		
LPCB quality mark	✘		
Suitable for steel tube	✓		
Suitable for thin-walled pipe	✓		
Suitable for stainless steel tube	✓		
Suitable for copper tube	✓		
Suitable for aluminium tube	✓		
Suitable for cast iron pipe	✓		
Suitable for plastic tube	✓		
Suitable for pipe coil	✓		
KIWA certified	✘		