




## UFH-0605MDSS02: 2-groups Manif. ss ,adjust.+flow met.+thermo,fill+dr. val., arv 2way



### Commercial information

- Adjustable flowmeters
- Adaptable brackets in composite
- Integrated air vent, drain and filling tap
- 1" connection with union nut
- Integrated control valves
- Compact design

### Certificates

### Applications

Heating, Cooling, Underfloor Heating

### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	5 55 Degrees celsius
Material	Stainless steel	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	0
Primary connection	Internal thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	2
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✗	Flow-through capacity	0 5 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✗	Width	120 Millimetre
Multi-zone manifold	✗	Height	190 Millimetre
With temperature limit	✗	Depth	370 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 6		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✗		
Temperature measurement supply	None		
Temperature measurement return	None		
With de-aeration	✓		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		

## Related products

Product code	GTIN	Description
UFH-CAB-I455	05414764400450	Henco Recessed manifold cabinet RAL9003 internal width 455MM
UFH-CAB-O385	05414764400450	Henco Surface mount cabinet RAL9003 internal width 385MM
UFH-CAB-O385Z	05414764400450	Henco Surface mount cabinet backless RAL9003 internal width 385MM
UFH-B0605-VN	05414764400450	Henco ball valve set 1"x3/4" with gasket nickel-plated b+r

### Image



Product code	GTIN	Description
UFH-BM0606-VN	05414764400450	Henco Ball valve set 1" x 1" with gasket, nickel-plated B+R

Image



19PK-1605	05414764400450	Henco Press to eurocone 16x3/4"
-----------	----------------	---------------------------------



19PK-2005	05414764400450	Henco Press to eurocone 20x3/4"
-----------	----------------	---------------------------------



19SK-1605	05414764400450	Henco Push fitting with eurocone connection 16x3/4"
-----------	----------------	---



19SK-2005	05414764400450	Henco Push fitting with eurocone connection 20x3/4"
-----------	----------------	---



EK15	05414764400450	Henco Nickel plated eurocone Ø15 (3/4" F)
------	----------------	---



19SK-1505	05414764400450	Henco Push fitting with eurocone connection 15x2,5"
-----------	----------------	---

